

Czech Module for datetime2 Package

Nicola L. C. Talbot (inactive)

2015-03-30 (v1.0)

This module is currently unmaintained and may be subject to change. If you want to volunteer to take over maintenance, contact me at <http://www.dickimaw-books.com/contact.html>

Abstract

This is the Czech language module for the datetime2 package. If you want to use the settings in this module you must install it in addition to installing datetime2. If you use babel or polyglossia, you will need this module to prevent them from redefining `\today`. The datetime2 `userregional` setting must be set to `text` or `numeric` for the language styles to be set. Alternatively, you can set the style in the document using `\DTMsetstyle`, but this may be changed by `\date<language>` depending on the value of the `userregional` setting.

I've copied the date style from `babel-czech's \today`.

I don't know if these settings are correct as I can't speak Czech. In particular, I don't know if the `czech` time style is correct. Currently this just uses the `default` time style. Please be aware that this may change. Whoever takes over maintenance of this module may change it as appropriate.

The new maintainer should add the line:

The Current Maintainer of this work is Name.

to the preamble part in `datetime2-czech.ins` where Name is the name of the maintainer(s) and replace the 'inactive' status to 'maintained'.

Currently there is only a regionless style.

1 The Code

1.1 UTF-8

This file contains the settings that use UTF-8 characters. This file is loaded if XeLaTeX or LuaLaTeX are used. Please make sure your text editor is set to UTF-8 if you want to view this code. Identify module

```
1\ProvidesDateTImodule{czech-utf8}[2015/03/30 v1.0]
```

`\DTMczechordinal`

```
2 \newcommand*{\DTMczechordinal}[1]{%  
3   \number#1.%  
4 }
```

`\DTMczechmonthname` Czech month names.

```
5 \newcommand*{\DTMczechmonthname}[1]{%  
6   \ifcase#1  
7   \or  
8   ledna%  
9   \or  
10  února%  
11  \or  
12  března%  
13  \or  
14  dubna%  
15  \or  
16  května%  
17  \or  
18  června%  
19  \or  
20  července%  
21  \or  
22  srpna%  
23  \or  
24  září%  
25  \or  
26  října%  
27  \or  
28  listopadu%  
29  \or  
30  prosince%  
31  \fi  
32 }
```

`\DTMczechMonthname` As above but capitalize.

```
33 \newcommand*{\DTMczechMonthname}[1]{%  
34   \ifcase#1  
35   \or  
36   Ledna%  
37   \or  
38   Února%  
39   \or  
40   Března%  
41   \or  
42   Dubna%  
43   \or  
44   Května%  
45   \or
```

```

46 Června%
47 \or
48 Července%
49 \or
50 Srpna%
51 \or
52 Září%
53 \or
54 Října%
55 \or
56 Listopadu%
57 \or
58 Prosince%
59 \fi
60 }

```

If abbreviated dates are supported, short month names should be likewise provided.

1.2 ASCII

This file contains the settings that use \LaTeX commands for non-ASCII characters. This should be input if neither XeLaTeX nor LuaLaTeX are used. Even if the user has loaded inputenc with utf8, this file should still be used not the `datetime2-czech-utf8.ldf` file as the non-ASCII characters are made active in that situation and would need protecting against expansion. Identify module

```
61 \ProvidesDateTimeModule{czech-ascii}[2015/03/30 v1.0]
```

If abbreviated dates are supported, short month names should be likewise provided.

`\DTMczechordinal`

```

62 \newcommand*{\DTMczechordinal}[1]{%
63   \number#1.%
64 }

```

`\DTMczechmonthname` Czech month names.

```

65 \newcommand*{\DTMczechmonthname}[1]{%
66   \ifcase#1
67   \or
68   ledna%
69   \or
70   \protect\'unora%
71   \or
72   b\protect\v{r}ezna%
73   \or
74   dubna%
75   \or
76   kv\protect\v{e}tna%
77   \or
78   \protect\v{c}ervna%

```

```

79 \or
80 \protect\v{c}ervence%
81 \or
82 srpna%
83 \or
84 z\protect\'a\protect\v{r}\protect\{\protect\i}%
85 \or
86 \protect\v{r}\protect\{\protect\i}jna%
87 \or
88 listopadu%
89 \or
90 prosince%
91 \fi
92 }

```

`\DTMczechMonthname` As above but start with a capital.

```

93 \newcommand*{\DTMczechMonthname}[1]{%
94 \ifcase#1
95 \or
96 Ledna%
97 \or
98 \protect\'Unora%
99 \or
100 B\protect\v{r}ezna%
101 \or
102 Dubna%
103 \or
104 Kv\protect\v{e}tna%
105 \or
106 \protect\v{C}ervna%
107 \or
108 \protect\v{C}ervence%
109 \or
110 Srpna%
111 \or
112 Z\protect\'a\protect\v{r}\protect\{\protect\i}%
113 \or
114 \protect\v{R}\protect\{\protect\i}jna%
115 \or
116 Listopadu%
117 \or
118 Prosince%
119 \fi
120 }

```

1.3 Main Czech Module (datetime2-czech.ldf)

Identify Module

```
121 \ProvidesDateTimeModule{czech}[2015/03/30 v1.0]
```

Need to find out if XeTeX or LuaTeX are being used.

```
122 \RequirePackage{ifxetex,ifluatex}
```

XeTeX and LuaTeX natively support UTF-8, so load `czech-utf8` if either of those engines are used otherwise load `czech-ascii`.

```
123 \ifxetex
```

```
124 \RequireDateTimeModule{czech-utf8}
```

```
125 \else
```

```
126 \ifluatex
```

```
127 \RequireDateTimeModule{czech-utf8}
```

```
128 \else
```

```
129 \RequireDateTimeModule{czech-ascii}
```

```
130 \fi
```

```
131 \fi
```

Define the `czech` style. The time style is the same as the `default` style provided by `datetime2`. This may need correcting. For example, if a 12 hour style similar to the `englishampm` (from the `english-base` module) is required.

Allow the user a way of configuring the `czech` and `czech-numeric` styles. This doesn't use the package wide separators such as `\dtm@datetimesep` in case other date formats are also required.

`\DTMczechdaymonthsep` The separator between the day and month for the text format.

```
132 \newcommand*{\DTMczechdaymonthsep}{\DTMtexorpdfstring{\protect~}{\space}}
```

`\DTMczechmonthyearsep` The separator between the month and year for the text format.

```
133 \newcommand*{\DTMczechmonthyearsep}{\space}
```

`\DTMczechdatetimesep` The separator between the date and time blocks in the full format (either text or numeric).

```
134 \newcommand*{\DTMczechdatetimesep}{\space}
```

`\DTMczechtimezonesep` The separator between the time and zone blocks in the full format (either text or numeric).

```
135 \newcommand*{\DTMczechtimezonesep}{\space}
```

`\DTMczechdatesep` The separator for the numeric date format.

```
136 \newcommand*{\DTMczechdatesep}{.}
```

`\DTMczechtimesep` The separator for the numeric time format.

```
137 \newcommand*{\DTMczechtimesep}{:}
```

Provide keys that can be used in `\DTMlangsetup` to set these separators.

```
138 \DTMdefkey{czech}{daymonthsep}{\renewcommand*{\DTMczechdaymonthsep}{#1}}
```

```
139 \DTMdefkey{czech}{monthyearsep}{\renewcommand*{\DTMczechmonthyearsep}{#1}}
```

```
140 \DTMdefkey{czech}{datetimesep}{\renewcommand*{\DTMczechdatetimesep}{#1}}
```

```
141 \DTMdefkey{czech}{timezonesep}{\renewcommand*{\DTMczechtimezonesep}{#1}}
```

```
142 \DTMdefkey{czech}{datesep}{\renewcommand*{\DTMczechdatesep}{#1}}
```

```
143 \DTMdefkey{czech}{timesep}{\renewcommand*{\DTMczechtimesep}{#1}}
```

TODO: provide a boolean key to switch between full and abbreviated formats if appropriate. (I don't know how the date should be abbreviated.)

Define a boolean key that determines if the time zone mappings should be used.

```
144 \DTMdefboolkey{czech}{mapzone}[true]{}
```

The default is to use mappings.

```
145 \DTMsetbool{czech}{mapzone}{true}
```

Define a boolean key that determines if the day of month should be displayed.

```
146 \DTMdefboolkey{czech}{showdayofmonth}[true]{}
```

The default is to show the day of month.

```
147 \DTMsetbool{czech}{showdayofmonth}{true}
```

Define a boolean key that determines if the year should be displayed.

```
148 \DTMdefboolkey{czech}{showyear}[true]{}
```

The default is to show the year.

```
149 \DTMsetbool{czech}{showyear}{true}
```

Define the czech style. (TODO: implement day of week?)

```
150 \DTMnewstyle
```

```
151 {czech}% label
```

```
152 {% date style
```

```
153   \renewcommand*\DTMdisplaydate[4]{%
```

```
154     \DTMifbool{czech}{showdayofmonth}
```

```
155     {\DTMczechordinal{##3}\DTMczechdaymonthsep}%
```

```
156     }%
```

```
157     \DTMczechmonthname{##2}%
```

```
158     \DTMifbool{czech}{showyear}%
```

```
159     {%
```

```
160       \DTMczechmonthyearsep
```

```
161       \number##1
```

```
162     }%
```

```
163   }%
```

```
164 }%
```

```
165 \renewcommand*\DTMdisplaydate[4]{%
```

```
166   \DTMifbool{czech}{showdayofmonth}
```

```
167   {%
```

```
168     \DTMczechordinal{##3}\DTMczechdaymonthsep
```

```
169     \DTMczechmonthname{##2}%
```

```
170     }%
```

```
171     {%
```

```
172       \DTMczechMonthname{##2}%
```

```
173       }%
```

```
174       \DTMifbool{czech}{showyear}%
```

```
175       {%
```

```
176         \DTMczechmonthyearsep
```

```
177         \number##1
```

```
178       }%
```

```
179     }%
```

```
180 }%
```

```

181 }%
182 {% time style (use default)
183   \DTMsettimestyle{default}%
184 }%
185 {% zone style
186   \DTMresetzones
187   \DTMczechzonemaps
188   \renewcommand*{\DTMdisplayzone}[2]{%
189     \DTMifbool{czech}{mapzone}%
190     {\DTMusezonemapordefault{##1}{##2}}%
191     {%
192       \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
193       \ifDTMshowzoneminutes\DTMczechtimestep\DTMtwodigits{##2}\fi
194     }%
195   }%
196 }%
197 {% full style
198   \renewcommand*{\DTMdisplay}[9]{%
199     \ifDTMshowdate
200       \DTMdisplaydate{##1}{##2}{##3}{##4}%
201       \DTMczechdatetimestep
202       \fi
203       \DTMdisplaytime{##5}{##6}{##7}%
204       \ifDTMshowzone
205         \DTMczechtimestep
206         \DTMdisplayzone{##8}{##9}%
207       \fi
208     }%
209   \renewcommand*{\DTMDisplay}[9]{%
210     \ifDTMshowdate
211       \DTMDisplaydate{##1}{##2}{##3}{##4}%
212       \DTMczechdatetimestep
213       \fi
214       \DTMdisplaytime{##5}{##6}{##7}%
215       \ifDTMshowzone
216         \DTMczechtimestep
217         \DTMdisplayzone{##8}{##9}%
218       \fi
219     }%
220 }%
    Define numeric style.
221 \DTMnewstyle
222 {czech-numeric}% label
223 {% date style
224   \renewcommand*{\DTMdisplaydate}[4]{%
225     \DTMifbool{czech}{showdayofmonth}%
226     {%
227       \number##3 % space intended
228       \DTMczechdatesep

```

```

229     }%
230     {}%
231     \number##2 % space intended
232     \DTMifbool{czech}{showyear}%
233     {%
234         \DTMczechdatesep
235         \number##1 % space intended
236     }%
237     {}%
238     }%
239     \renewcommand*\DTMdisplaydate[4]{\DTMdisplaydate{##1}{##2}{##3}{##4}}%
240 }%
241 {% time style
242     \renewcommand*\DTMdisplaytime[3]{%
243         \number##1
244         \DTMczechtimesep\DTMtwodigits{##2}%
245         \ifDTMshowseconds\DTMczechtimesep\DTMtwodigits{##3}\fi
246     }%
247 }%
248 {% zone style
249     \DTMresetzones
250     \DTMczechzonemaps
251     \renewcommand*\DTMdisplayzone[2]{%
252         \DTMifbool{czech}{mapzone}%
253         {\DTMusedzonemapordefault{##1}{##2}}%
254         {%
255             \ifnum##1<0\else+\fi\DTMtwodigits{##1}%
256             \ifDTMshowzoneminutes\DTMczechtimesep\DTMtwodigits{##2}\fi
257         }%
258     }%
259 }%
260 {% full style
261     \renewcommand*\DTMdisplay[9]{%
262         \ifDTMshowdate
263             \DTMdisplaydate{##1}{##2}{##3}{##4}%
264             \DTMczechdatetimesep
265             \fi
266             \DTMdisplaytime{##5}{##6}{##7}%
267             \ifDTMshowzone
268                 \DTMczechtimezonesep
269                 \DTMdisplayzone{##8}{##9}%
270             \fi
271         }%
272     \renewcommand*\DTMdisplay{\DTMdisplay}%
273 }

```

`\DTMczechzonemaps` The time zone mappings are set through this command, which can be redefined if extra mappings are required or mappings need to be removed.

```

274 \newcommand*\DTMczechzonemaps{%
275     \DTMdefzonemap{01}{00}{CET}%

```



```
276 \DTMdefzonemap{02}{00}{CEST}%
277 }
```

Switch style according to the `userregional` setting.

```
278 \DTMifcaseregional
279 {}% do nothing
280 {\DTMsetstyle{czech}}
281 {\DTMsetstyle{czech-numeric}}
```

Redefine `\dateczech` (or `\date<dialect>`) to prevent babel from resetting `\today`. (For this to work, babel must already have been loaded if it's required.)

```
282 \ifcsundef{date\CurrentTrackedDialect}
283 {%
284   \ifundef\dateczech
285   {% do nothing
286   }%
287   {%
288     \def\dateczech{%
289       \DTMifcaseregional
290       {}% do nothing
291       {\DTMsetstyle{czech}}%
292       {\DTMsetstyle{czech-numeric}}%
293     }%
294   }%
295 }%
296 {%
297   \csdef{date\CurrentTrackedDialect}{%
298     \DTMifcaseregional
299     {}% do nothing
300     {\DTMsetstyle{czech}}%
301     {\DTMsetstyle{czech-numeric}}
302   }%
303 }%
```

Change History

1.0
General: Initial release 1, 3, 4

Index

D			
\DTMczechdatesep	5	\DTMczechordinal	2, 3
\DTMczechdatetimesep	5	\DTMczechtimesep	5
\DTMczechdaymonthsep	5	\DTMczechtimezonesep	5
\DTMczechMonthname	2, 4	\DTMczechzonemaps	8
\DTMczechmonthname	2, 3		
\DTMczechmonthyearsep	5	U	
		useregional	1, 9