

NAME

pdftoppm – Portable Document Format (PDF) to Portable Pixmap (PPM) converter (version 3.04)

SYNOPSIS

pdftoppm [options] *PDF-file* *PPM-root*

DESCRIPTION

Pdftoppm converts Portable Document Format (PDF) files to color image files in Portable Pixmap (PPM) format, grayscale image files in Portable Graymap (PGM) format, or monochrome image files in Portable Bitmap (PBM) format.

Pdftoppm reads the PDF file, *PDF-file*, and writes one PPM file for each page, *PPM-root-nnnnnn.ppm*, where *nnnnnn* is the page number. If *PPM-root* is '-', the image is sent to stdout (this is probably only useful when converting a single page).

CONFIGURATION FILE

Pdftoppm reads a configuration file at startup. It first tries to find the user's private config file, *~/.xpdfrc*. If that doesn't exist, it looks for a system-wide config file, typically */usr/local/etc/xpdfrc* (but this location can be changed when pdftoppm is built). See the **xpdfrc(5)** man page for details.

OPTIONS

Many of the following options can be set with configuration file commands. These are listed in square brackets with the description of the corresponding command line option.

-f *number*

Specifies the first page to convert.

-l *number*

Specifies the last page to convert.

-r *number*

Specifies the resolution, in DPI. The default is 150 DPI.

-mono Generate a monochrome PBM file (instead of a color PPM file).

-gray Generate a grayscale PGM file (instead of a color PPM file).

-freetype *yes / no*

Enable or disable FreeType (a TrueType / Type 1 font rasterizer). This defaults to "yes". [config file: **enableFreeType**]

-aa *yes / no*

Enable or disable font anti-aliasing. This defaults to "yes". [config file: **antialias**]

-aaVector *yes / no*

Enable or disable vector anti-aliasing. This defaults to "yes". [config file: **vectorAntialias**]

-opw *password*

Specify the owner password for the PDF file. Providing this will bypass all security restrictions.

-upw *password*

Specify the user password for the PDF file.

-q Don't print any messages or errors. [config file: **errQuiet**]

-v Print copyright and version information.

-h Print usage information. (**-help** and **--help** are equivalent.)

EXIT CODES

The Xpdf tools use the following exit codes:

- 0 No error.
- 1 Error opening a PDF file.
- 2 Error opening an output file.

- 3 Error related to PDF permissions.
- 99 Other error.

AUTHOR

The pdftoppm software and documentation are copyright 1996-2014 Glyph & Cog, LLC.

SEE ALSO

**xpdf(1), pdftops(1), pdftotext(1), pdftohtml(1), pdfinfo(1), pdffonts(1), pdfdetach(1), pdftopng(1),
pdfimages(1), xpdfrc(5)**
<http://www.foolabs.com/xpdf/>