

The `ccaption` package*

Peter Wilson
Catholic University of America
Now at peter.r.wilson@boeing.com

2003/11/14

Abstract

The `ccaption` package enables restyling of captions and provides for ‘continuation’ captions, unnumbered captions, bilingual captions, and an ‘anonymous’ caption (a legend) that can be used in any environment. It also provides commands to define captions that can be used outside float environments as well as a mechanism for creating new types of float environments and subfloats.

The package has been tested in conjunction with the `tocloft` rotating, `caption2`, `sidecap`, `subfigure`, `endfloat` and `hyperref` packages.

Contents

1	Introduction	2
2	The <code>ccaption</code> package	3
2.1	Options	3
2.2	Changing the caption style	3
2.3	Continuation captions and legends	6
2.4	Bilingual captions	11
2.5	Use with the <code>subfigure</code> package	13
2.6	Use with the <code>endfloat</code> package	14
2.7	New float environments	15
2.8	How LaTeX makes captions	19
2.9	Changing the numbering scheme	22
2.10	Captions with footnotes	23
2.11	Multiple floats	24
2.12	Where LaTeX puts floats	25

*This file (`ccaption.dtx`) has version number v3.1c, last revised 2003/11/14.

3	The package code	29
3.1	Caption styling	30
3.2	Continuation captions and legends	33
3.3	Non-float captions	35
3.4	Bilingual captions	35
3.5	The subfigure options	38
3.5.1	Option subfigure20	38
3.5.2	Option subfigure21	42
3.6	New floats	47
A	The perils of empty	53

List of Tables

1	Redesigned table caption style	5
2	A multi-part table	7
3	Another table	8
	Legendary table (toc 1)	8
	Legendary table (toc 2)	8
4	Float placement parameters	27

List of Figures

1	Long	12
1	Lang	12
2	Long English	12
	Lang Deutsch	12
3	Short English	12
4	A picture is worth a thousand words	21
5	A different kind of figure caption	22
6	Float with two illustrations	24
7	Illustration 3	25
8	Illustration 4	25

1 Introduction

Some publishers require and some authors prefer captioning styles other than the one style provided by LaTeX. The `ccaption` package provides the tools to design your own captioning styles.

Some publishers require that documents that include multi-part tables use a *continuation caption* on all but the first part of the multi-part table. For the times where such a table is specified by the author as a set of tables, the `ccaption` package provides a simple ‘continuation’ caption command to meet this requirement. It also provides a facility for an ‘anonymous’ caption which can be used in any float

environment. The package has been tested with the `rotating`, `caption2`, `sidecap`, `subfigure` (v2.0 and the current version), `endfloat` and the `hyperref` packages.

Captions can be defined that are suitable for use in non-float environments, such as placing a picture in a minipage and captioning it just as though it had been put into a normal figure environment. Further, a mechanism is provided for defining new float environments.

These facilities were originally developed in support of a suite for typesetting ISO international standard [Wil96], but they are generally applicable. This manual is typeset according to the conventions of the LaTeX DOCSTRIP utility which enables the automatic extraction of the LaTeX macro source files [GMS94].

Section 2 provides a short overview of the commands in the package and shows some examples of their use. This section also gives examples of how LaTeX's captioning style can be changed to a limited extent without the use of any package and provides general information on floats. For a more comprehensive description of floats read Keith Reckdahl's excellent *Using Imported Graphics in LaTeX2e* [Rec97], although this was written before the advent of the `ccaption` package. The implementation is given in Section 3.

2 The `ccaption` package

2.1 Options

The package may take one or more options, depending on which other packages are used in conjunction with `ccaption`. The options are designed so that the package loading order does not matter. The current options are:

`subfigure` for use with the current version of Steven Douglas Cochran's `subfigure` package [Coc95].

`subfigure20` when used together with the old version 2.0 of the `subfigure` package.

`caption2` when used together with Harald Axel Sommerfeldt's `caption` or `caption2` package [Som95].

`titles` When new floats, and their corresponding 'List of...', are defined, the list headings may be individually configured. The `titles` option disables the configuration mechanism. This may be useful if, say, the `fncychap` package is used to redefine the appearance of chapter titles.

For example, if the package is being used with both `subfigure` version 2.1 and `caption` then it should be called as:

```
\usepackage[subfigure,caption2]{ccaption}
```

2.2 Changing the caption style

The discussion in §2.8 includes example methods for changing the typeset appearance of captions without the benefit of any package. The `caption2` and `caption`

packages provides a set of predefined captioning styles, and the `ccaption` package also provides an easy means of changing the style.

The style of subcaptions is controlled by the `subfigure` package.

Note that if the `caption2` option is used then it is assumed that the `caption(2)` package is being used and the facilities described in this section are unavailable.

`\captiondelim` The default captioning style is to put a delimiter in the form of a colon between the caption number and the caption title. The command `\captiondelim{<delim>}` can be used to change the delimiter. For example, to have an en-dash instead `\captiondelim{--}` will do the trick. Notice that no space is put between the delimiter and the title unless it is specified in the `<delim>` parameter. The package initially specifies `\captiondelim{: }` to give the normal delimiter.

`\captionnamefont` The `` specified by `\captionnamefont{}` is used for typesetting the caption name; that is, the first part of the caption upto and including the delimiter (e.g., the portion ‘Table 3:’). `` can be any kind of font specification and/or command and/or text. This first part of the caption is treated like: `{ Table 3; }`, so font declarations, not font text-style commands, are needed, like `\captionnamefont{\Large\sffamily}` to specify a large sans-serif font. The package initially specifies `\captionnamefont{}` to give the normal font.

`\captiontitlefont` Similarly, the `` specified by `\captiontitlefont{}` is used for typesetting the title text of a caption. For example, `\captiontitlefont{\itshape}` for an italic title text. The package initially specifies `\captiontitlefont{}` to give the normal font.

`\captionstyle` By default the name and title of a caption are typeset as a block (non-indented) paragraph. `\captionstyle{<style>}` can be used to alter this. Sensible values for `<style>` are: `\centering`, `\raggedleft` or `\raggedright` for styles corresponding to these declarations. The `\centerlastline` style gives a block paragraph but with the last line centered. The package initially specifies `\captionstyle{}` to give the normal block paragraph style.

`\hangcaption` The command `\hangcaption` will cause captions to be typeset with the second and later lines of a multiline caption title indented by the width of the caption name. The command `\indentcaption{<length>}` will indent title lines after the first by `<length>`. These commands are independent of the `\captionstyle{...}`. Note that a caption will not be simultaneously hung and indented. The `\normalcaption` command undoes any previous `\hangcaption` or `\indentcaption` command. The package initially specifies `\normalcaption` to give the normal non-indented paragraph style.

`\changecaptionwidth` Issuing the command `\changecaptionwidth` will cause the captions to be typeset within a total width `<length>` as specified by `\captionwidth{<length>}`. Issuing the command `\normalcaptionwidth` will cause captions to be typeset as normal full width captions. The package initially specifies `\normalcaptionwidth` and `\captionwidth{\linewidth}` to give the normal width. If a caption is being set within the side captioned environments from the `sidecap` package [NiGa98] then it must be a `\normalcaptionwidth` caption.

`\precaption` The commands `\precaption{<pretext>}` and `\postcaption{<posttext>}` specify `<pretext>` and `<posttext>` that will be processed at the start and end of a caption.

Table 1
REDESIGNED TABLE CAPTION STYLE

three	III
five	V
eight	VIII

For example

```
\precaption{\rule{\linewidth}{0.4pt}\par}
\postcaption{\rule{\linewidth}{0.4pt}}
```

will draw a horizontal line above and below the captions. The package initially specifies `\precaption{}` and `\postcaption{}` to give the normal appearance.

If any of the above commands are used in a float, or other, environment their effect is limited to the environment. If they are used in the preamble or the main text, their effect persists until replaced by a similar command with a different parameter value. The commands do not affect the appearance of the title in any **List of...**

`\` The normal LaTeX command `\[<length>]` can be used within the caption text to start a new line. Remember that `\` is a fragile command, so if it is used within text that will be added to a **List of...** it must be protected. As examples:

```
\caption{Title with a \protect\ new line in both the body and List of}
\caption[List of entry with no new line]{Title with a \ new line}
\caption[List of entry with a \protect\ new line]{Title text}
```

Effectively, a caption is typeset as though it were:

```
\precaption
{NAME NUMBER \captiondelim}
\captionstyle\captiontitlefont THE TITLE}
\postcaption
```

Replacing the above commands by their defaults leads to the simple format:

```
{NAME NUMBER: }{THE TITLE}
```

As well as using the styling commands to make simple changes to the captioning style more noticeable modifications can also be made. To change the captioning style so that the name and title are typeset in a sans font it is sufficient to do:

```
\captionnamefont{\sffamily}
\captiontitlefont{\sffamily}
```

A more obvious change in styling is shown in table 1, which was coded as:

```
\begin{table}
\centering
\captionnamefont{\sffamily}
\captiondelim{}
\captionstyle{\}
```

```

\captiontitlefont{\scshape}
\setlength{\belowcaptionskip}{10pt}
\caption{Redesigned table caption style} \label{tab:style}
\begin{tabular}{lr} \hline
...
\end{table}

```

This leads to the approximate caption format (processed within `\centering`):

```
{\sffamily NAME NUMBER}{\ \scshape THE TITLE}
```

Note that the newline command (`\`) cannot be put in the first part of the format (i.e., the `{\sffamily NAME NUMBER}`); it has to go into the second part, which is why it is specified via `\captionstyle{\}` and not `\captiondelim{\}`.

If a mixture of captioning styles will be used you may want to define a special caption command for each non-standard style. For example for the style of the caption in table 1:

```

\newcommand{\mycaption}[2][\@empty]{%
  \captionnamefont{\sffamily\hfill}
  \captiondelim{\hfill}
  \captionstyle{\centerlastline\}
  \captiontitlefont{\scshape}
  \setlength{\belowcaptionskip}{10pt}
  \ifx #1\@empty \caption{#2}\else \caption[#1]{#2}}

```

NOTE: Any code that involves the @ sign must be either in a package (`.sty`) file or enclosed between a `\makeatletter ... \makeatother` pairing.

The code for the table 1 example can now be written as:

```

\begin{table}
\centering
\mycaption{Redesigned table caption style} \label{tab:style}
\begin{tabular}{lr} \hline
...
\end{table}

```

Note that in the code for `\mycaption` I have added two `\hfill` commands and `\centerlastline` compared with the original specification. It turned out that the original definitions worked for a single line caption but not for a multiline caption. The additional commands makes it work in both cases, forcing the name to be centered as well as the last line of a multiline title, thus giving a balanced appearance.

2.3 Continuation captions and legends

`\contcaption` The `\contcaption{<text>}` command can be used to put a ‘continuation’ or ‘concluded’ caption into a float environment. It neither increments the float number

Table 2: A multi-part table

just a single line	1
--------------------	---

Table 2: Continued

just a single line	2
--------------------	---

nor makes any entry into a float listing, but it does repeat the numbering of the previous `\caption` command.

Table 2 illustrates the use of the `\contcaption` command. The table was produced from the following code.

```
\begin{table}
\centering
\caption{A multi-part table} \label{tab:m}
\begin{tabular}{lc} \hline
just a single line & 1 \\ \hline
\end{tabular}
\end{table}
```

```
\begin{table}
\centering
\contcaption{Continued}
\begin{tabular}{lc} \hline
just a single line & 2 \\ \hline
\end{tabular}
\end{table}
```

```
\begin{table}
\centering
\contcaption{Concluded}
\begin{tabular}{lc} \hline
just a single line & 3 \\ \hline
\end{tabular}
\end{table}
```

`\legend` The `\legend{text}` command is intended to be used to put an anonymous caption into a float environment, but may be used anywhere.

For example, the following code was used to produce the two-line table 3. The `\legend` command can be used within a float independently of any `\caption` command.

```
\begin{table}
\centering
```

Table 2: Concluded
just a single line 3

<u>Table 3: Another table</u>	
A legendary table	5
with two lines	6

The legend

<u>Legendary table</u>	
An anonymous table	5
with two lines	6

```
\caption{Another table} \label{tab:legend}
\begin{tabular}{lc} \hline
  A legendary table & 5 \\
  with two lines    & 6 \\ \hline
\end{tabular}
\legend{The legend}
\end{table}
```

Title legend

This is a marginal note with a legend.

Captioned floats are usually thought of in terms of the `table` and `figure` environments. There can be other kinds of float. As perhaps a more interesting example, the following code produces the titled marginal note which should be displayed near here.

```
\marginpar{\legend{Title legend}
           This is a marginal note with a legend.}
```

You can even

Legend in running text

use the `\legend` command in running text, as has been done in this sentence, but I'm not sure why one might want to do that as LaTeX already provides the `center` environment.

If you want the legend text to be included in the **List of...** use the `\addcontentsline` command in conjunction with the `\legend`. For example:

```
\addcontentsline{lot}{table}{Titling text} % left justified
\addcontentsline{lot}{table}{\protect\numberline{}Titling text} % indented
```

The first of these forms will align the first line of the legend text under the normal table numbers. The second form will align the first line of the legend text under the normal table titles. In either case, second and later lines of a multi-line text will be aligned under the normal title lines.

As an example, the **Legendary table** is produced by the following code:

```
\begin{table}
\centering
```

Table: *Named legendary table*

seven	VII
eight	VIII

```

\captiontitlefont{\sffamily}
\legend{Legendary table}
\addcontentsline{lot}{table}{Legendary table (toc 1)}
\addcontentsline{lot}{table}{\protect\numberline{ }Legendary table (toc 2)}
\begin{tabular}{lc} \hline
  An anonymous table & 5 \\
  with two lines    & 6 \\ \hline
\end{tabular}
\end{table}

```

Look at the List of Tables to see how the two forms of `\addcontentsline` are typeset.

`\abovelegendskip` Correspondingly to the `\abovecaptionskip` and `\belowcaptionskip` commands associated with the `\caption` command, the spacing before and after a legend is controlled by the `\abovelegendskip` and `\belowlegendskip` commands. If necessary, these can be modified via the `\setlength` command. By default these are defined to give a half baseline spacing before and after the legend.

`\namedlegend` As a convenience, the `\namedlegend[<short-title>]{<long-title>}` command is like the `\caption` command except that it does not number the caption and, by default, puts no entry into a **List of...** file. Like the `\caption` command, it picks up the name to be prepended to the title text from the float environment in which it is called (e.g., it may use `\tablename` if called within a `table` environment). The following code is the source of the *Named legendary table*.

```

\begin{table}
\centering
\captionnamefont{\sffamily}
\captiontitlefont{\itshape}
\namedlegend{Named legendary table}
\begin{tabular}{lr} \hline
seven & VII \\
eight & VIII \\ \hline
\end{tabular}
\end{table}

```

`\fleg@type` The macro `\fleg@type{<name>}`, where `type` is the name of a float environment (e.g., `table`) is called by the `\namedlegend` macro. It is provided as a hook that defines the `<name>` to be used as the name in `\namedlegend`. Two defaults are provided, namely:

```

\newcommand{\fleg@table}{\tablename}
\newcommand{\fleg@figure}{\figurename}

```

which may be altered via `\renewcommand` if desired (put between a `\makeatletter` and `\makeatother` pair if done in the document).

`\flegtoc@type`

The macro `\flegtoc@type{<title>}`, where `type` is the name of a float environment (e.g., `table`) is called by the `\namedlegend` macro. It is provided as a hook that can be used to add `<title>` to the `listof` file. By default it is defined to do nothing, and can be changed via `\renewcommand`. For instance, it could be changed for tables as:

```
\makeatletter
\renewcommand{\flegtoc@table}[1]{%
  \addcontentsline{lot}{table}{#1}}
\makeatother
```

`\newfixedcaption`

`\renewfixedcaption`

`\providfixedcaption`

The `\legend` command produces a plain, unnumbered heading. It can also be useful sometimes to have named and numbered captions outside a floating environment, perhaps in a `minipage` if you want the table or picture to appear at a precise location in your document.

The `\newfixedcaption[<capcommand>]{<command>}{<env>}` command, and its friends, can be used to create a new captioning `<command>` that may be used outside the float environment `<env>`. Both the environment `<env>` and a captioning command, `<capcommand>`, for that environment must have been defined before calling `\newfixedcaption`. Note that `\namedlegend` can be used as `<capcommand>`.

The `\renewfixedcaption` and `\providfixedcaption` commands take the same arguments as `\newfixedcaption`; the three commands are analagous to those in the `\newcommand` family.

For example, to define a new `\figcaption` command for captioning pictures outside the `figure` environment, do

```
\newfixedcaption{\figcaption}{figure}
```

The optional `<capcommand>` argument is the name of the float captioning command that is being aliased. It defaults to `\caption`. As another example, where the optional argument is required, if you want to create a new continuation caption command for non-floating tables, say `\ctabcaption`, then do

```
\newfixedcaption[\contcaption]{\ctabcaption}{table}
```

Captioning commands created by `\newfixedcaption` will be named and numbered in the same style as the original `<capcommand>`, can be given a `\label`, and will appear in the appropriate **List of . . .**. They can also be used within floating environments, but will not use the environment name as a guide to the caption name or entry into the **List of . . .**. For example, using `\ctabcaption` in a `figure` environment will still produce a **Table. . .** named caption.

Sometimes captions are required on the opposite page to a figure, and `\newfixedcaption` can be useful in this context. For example, if figure captions should be placed on an otherwise empty page immediately before the actual figure, then this can be accomplished by the following hack:

```
\newfixedcaption{\figcaption}{figure}
```

```

...
\afterpage{% fill current page then flush pending floats
\clearpage
\begin{midpage} % vertically center the caption
\figcaption{The caption} % the caption
\end{midpage}
\clearpage
\begin{figure}THE FIGURE, NO CAPTION HERE\end{figure}
\clearpage
} % end of \afterpage

```

Note that the `afterpage` package is required, which is part of the required tools bundle. The `midpage` package supplies the `midpage` environment, which can be simply defined as:

```
\newenvironment{midpage}{\vspace*{\fill}}{\vspace*{\fill}}
```

The code might need adjusting to meet your particular requirements. The `nextpage` package might also be useful in this context as it provides a `\cleartoevenpage` command which ensures that you get to the next even-numbered page (the `\cleardoublepage` gets you to the next odd-numbered page and `\clearpage` gets you to the next page which may be odd or even).

2.4 Bilingual captions

Some documents require bilingual (or more) captions. The package provides a set of commands for bilingual captions. Extensions to the set, perhaps to support trilingual captioning, are left as an exercise for the document author.

`\bitwounumcaption` Bilingual captions can be typeset by the `\bitwounumcaption` command. This takes 6 arguments as:

```
\bitwounumcaption[⟨label⟩]{⟨short-1⟩}{⟨long-1⟩}{⟨NAME⟩}{⟨short-2⟩}{⟨long-2⟩}
```

The first, optional argument `⟨label⟩`, is the name of a label, if required. `⟨short-1⟩` and `⟨long-1⟩` are the short (i.e., equivalent to the optional argument to the `\caption` command) and long caption texts for the main language of the document. The value of the `⟨NAME⟩` argument is used as the caption name for the second language caption, while `⟨short-2⟩` and `⟨long-2⟩` are the short and long caption texts for the second language. For example, if the main and secondary languages are English and German and a figure is being captioned:

```
\bitwounumcaption{Short}{Long}{Bild}{Kurz}{Lang}
```

If the short title text(s) is not required, then leave the appropriate argument(s) either empty or as one or more spaces, like:

```
\bitwounumcaption[fig:bi1]{}{Long}{Bild}{ }{Lang}
```

Both language texts are entered into the appropriate List of ..., and both texts are numbered.

Figure 1 is an example of using the above code.

EXAMPLE FIGURE WITH BITWONUMCAPTION

Figure 1: Long
Bild 1: Lang

EXAMPLE FIGURE WITH BIONENUMCAPTION

Figure 2: Long English
Bild 2: Lang Deutsch

The `\bionenumcaption` command takes the same arguments as `\bitwonumcaption`. The difference between the two commands is that `\bionenumcaption` does not number the second language text in the List of. Figure 2 is an example of using `\bionenumcaption`.

`\bicaption` When bilingual captions are typeset via the `\bicaption` command the second language text is not put into the List of. . . . The command takes 5 arguments as: `\bicaption[⟨label⟩]{⟨short-1⟩}{⟨long-1⟩}{⟨NAME⟩}{⟨long-2⟩}`

The optional `⟨label⟩` is for a label if required. `⟨short-1⟩` and `⟨long-1⟩` are the short and long caption texts for the main language of the document. The value of the `⟨NAME⟩` argument is used as the caption name for the second language caption. The last argument, `⟨long-2⟩`, is the caption text for the second language (which is not put into the List of). For example, if the main and secondary languages are English and German:

```
\bicaption{Short}{Long}{Bild}{Langlauf}
```

If the short title text is not required, then leave the appropriate argument either empty or as one or more spaces.

Figure 3 is an example of using `\bicaption` and was produced by the following code:

```
\begin{figure}
\centering
EXAMPLE FIGURE WITH A RULED BICAPTION
\precaption{\rule{\linewidth}{0.4pt}\par}
\midbicaption{\precaption{}\postcaption{\rule{\linewidth}{0.4pt}}}{
\bicaption[fig:bi2]{Short English}{Longingly}{Bild}{Langlauf}
\end{figure}
```

`\bicontcaption` Bilingual continuation captions can be typeset via the `\bicontcaption` command. In this case, neither language text is put into the List of. . . . This command

EXAMPLE FIGURE WITH A RULED BICAPTION

Figure 3: Longingly
Bild 3: Langlauf

takes 3 arguments as:

`\bicontcaption{⟨long-1⟩}{⟨NAME⟩}{⟨long-2⟩}`

⟨long-1⟩ is the caption text for the main language of the document. The value of the ⟨NAME⟩ argument is used as the caption name for the second language caption. The last argument, ⟨long-2⟩, is the caption text for the second language. For example, if the main and secondary languages are again English and German:

`\bicontcaption{Continued}{Bild}{Fortgefahren}`

`\midbication`

The bilingual captions are implemented by calling `\caption` twice, once for each language. The command `\midbication{⟨midtext⟩}`, which is similar to the `\precaption` and `\postcaption` commands, is executed just before calling the second `\caption`. Among other things, this can be used to modify the style of the second caption with respect to the first. For example, if there is normally a line above and below normal captions, it is probably undesirable to have a double line in the middle of a bilingual caption. So, for bilingual captions the following may be done within the float before the caption:

```
\precaption{\rule{\linewidth}{0.4pt}\par}
\postcaption{}
\midbication{\precaption{}\postcaption{\rule{\linewidth}{0.4pt}}}
```

This sets a line before the first of the two captions, then the `\midbication{...}` nulls the pre-caption line and adds a post-caption line for the second caption. The package initially specifies `\midbication{}`.

2.5 Use with the subfigure package

The `subfigure` package enables the captioning of sub-figures within a larger figure, and similarly for tables. If a figure that includes sub-figures is itself continued then it may be desirable to continue the captioning of the sub-figures. For example, if Figure 3 has three sub-figures, say A, B and C, and Figure 3 is continued then the sub-figures in the continuation should be D, E, etc.

`\contsubtop`
`\contsubbottom`

The command `\contsubtop[⟨list-entry⟩][⟨subcaption⟩]{⟨text⟩}` will continue the sub-caption numbering scheme across (continued) floats, putting the ⟨subcaption⟩ at the top of the ⟨text⟩. If both optional arguments are supplied, ⟨list-entry⟩ will be the entry in the List of... and ⟨subcaption⟩ will be used as the text for the subcaption. The `\contsubbottom` command is similar but puts the ⟨subcaption⟩ at the bottom of the ⟨text⟩. In either case, the main caption can be at the top or bottom of the float.

`\subconcluded`

The `\subconcluded` command is used to indicate that the continued (sub) float has been concluded and the numbering scheme is reinitialized. The command should be placed immediately before the end of the last continued environment.

`\subtop`
`\subbottom`

The command `\subtop[⟨list-entry⟩][⟨subcaption⟩]{⟨text⟩}` is in addition to the `subfigure` package commands `\subfigure` and `\subtable`. It puts the ⟨subcaption⟩ at the top of the ⟨text⟩, and similarly `\subbottom[⟨subcaption⟩]{⟨text⟩}` puts ⟨subcaption⟩ at the bottom of the ⟨text⟩.

For example:

```

\begin{figure}
\subbottom{...} % captioned as (a) below
\subbottom{...} % captioned as (b) below
\caption{...}
\end{figure}
\begin{figure}
\contsubtop{...} % captioned as (c) above
\contsubtop{...} % captioned as (d) above
\contcaption{Concluded}
\subconcluded
\end{figure}
...
\begin{table}
\caption{...}
\subtop{...} % captioned as (a) above
\subbottom{...} % captioned as (b) below
\end{table}

```

Depending on the age of your LaTeX distribution, you may find that you have either version 2.0 or a later version of the `subfigure` package. If you have version 2.0, then call the `ccaption` package as:

```

\usepackage[subfigure20]{ccaption}, otherwise as:
\usepackage[subfigure]{ccaption}.

```

Version 2.1 of the `subfigure` package uses many package options some of which had been provided as commands in version 2.0. The `ccaption` commands just described apply to the current version. They also apply to version 2.0 except that the `\...top` and `\...bottom` commands do *not* take the first optional argument as: `\...top[<subcaption>]{<text>}`.

Both versions of `subfigure` provide the commands `\subfigure` and `\subtable` which may be used with the `ccaption` package (which also provides matching `\contsubfigure` and `\contsubtable` commands) but I recommend using the generic `\...top` and `\...bottom` commands instead. One reason being that the generic commands can be used for subcaptions in new kinds of floats, whereas the specific `\...figure` and `\...table` commands cannot. In the current version of `subfigure` the placement (top or bottom) of the subcaptions and the expected placement of the main caption are set by package options. Using these options in conjunction with the `ccaption` package may cause unexpected results, which is another reason for using the generic subcaption commands.

2.6 Use with the `endfloat` package

The `endfloat` package [McCG95] has the capability of putting all floats at the end of the printed document and inserting comments in the main text that a float should be placed about *there*. There is a slight problem if continuation captions are used in conjunction with the package, as `endfloat` effectively numbers each float whether or not it is captioned, and thus will increment the numbering for and continued float.

One way of getting `endfloat` and `ccaption` continued captions to cooperate is to put the following in the document preamble (modifying or extending it to suit):

```
\newcommand{\contendfloat}{}
\renewcommand{\tableplace}{%
  \begin{center}
    [\tablename~\theposttbl\ \contendfloat\ about here.]
  \end{center}
\newenvironment{conttable}{%
  \addtocounter{posttbl}{-1}%
  \def\contendfloat{(continued)}}{}
\renewcommand{\figureplace}{%
  \begin{center}
    [\figurename~\thepostfig\ \contendfloat\ about here.]
  \end{center}
\newenvironment{contfigure}{%
  \addtocounter{postfig}{-1}%
  \def\contendfloat{(continued)}}{}}
```

and then, for a table, in the document:

```
...
\begin{table}
\caption{...}
...
\end{table}
...
\begin{conttable}
\begin{table}
\contcaption{Continued}
...
\end{table}
\end{conttable}
```

and similarly for any continued figures.

2.7 New float environments

The commands in the previous sections have been tested with the `caption2` and `rotating` packages. They will most likely fail if used with the `float` package because of the way this package redefines the basic `\caption` command.

The `float` package, developed by Anselm Lingnau [Lin95], provides a simple scheme for creating new kinds of floats with a variety of captioning styles. Unfortunately the package does not effectively separate the float creation aspects and the captioning styles. I have therefore included in the `ccaption` package a poor man's version of some aspects of the float creation elements that are in `float`. Both the commands and their coding differ from those in the `float` package.

`\newfloatlist` The command `\newfloatlist` [*<within>*]{*<fenv>*}{*<ext>*}{*<listname>*}{*<capname>*}

creates both a new kind of floating environment called $\langle fenv \rangle$ and a new kind of ‘List of’ for $\langle fenv \rangle$; the title of this new listing is $\langle listname \rangle$. A caption within the environment will be written out to a file with extension $\langle ext \rangle$. The caption, if present, will start with $\langle capname \rangle$. For example, if this command had been used to create the `figure` environment for the `article` class it would have been used as (remembering that LaTeX uses `\listfigurename` to store the ‘List of Figures’ text and `\figurename` to store the ‘Figure’ text):

```
\newfloatlist{figure}{lof}{\listfigurename}{\figurename}
and the command \listoffigure (generated by \newfloatlist) would typeset
the List of Figures.
```

The optional $\langle within \rangle$ argument can be used if you want the captions to be numbered within a particular document division, as figures are within the `book` and `report` classes with the numbering starting afresh with each new chapter. Creating the figure environment for either of these classes would have used:

```
\newfloatlist[chapter]{figure}{lof}{\listfigurename}{\figurename}
```

The captioning style for floats defined with `\newfloatlist` is the same as for figures and tables in the standard classes.

The `\newfloatlist` command generates several new commands that you can use for styling the new listing, similar to the facilities given by the `tocloft` package [Wil01]; for more detailed information you may wish to read the `tocloft` documentation. For ease of explanation, assume that the command was called as `\newfloatlist{X}{Z}{flist}{fcap}`, so that X corresponds to the name of the new environment $\langle fenv \rangle$ and Z corresponds to the file extension $\langle ext \rangle$. The following float environment and commands are then created.

X The new float environment is called X , and can be used as either `\begin{X}` or `\begin{X*}`, with the matching `\end{X}` or `\end{X*}`.

`\listofX` `\listofX` is similar to `\listoffigures`, etc., in that it typesets the new listing, and heads the list with the value of `flist`.

$Zdepth$ The $Zdepth$ counter is analogous to the standard `tocdepth` counter in that it specifies that entries in the new listing should not be typeset if their numbering level is greater than $Zdepth$. The default definition is `\setcounter{Zdepth}{1}`. To have a subfloat of Z appear in the listing do `\setcounter{Zdepth}{2}`.

`\cftmarkZ` This macro sets the appearance of the running heads on the new listing pages. The default definition gives the same appearance as for the LoF or LoT.

`\cftbeforeZtitleskip` The lengths `\cftbeforeZtitleskip` and `\cftafterZtitleskip` control the vertical spacing before and after the title of the new listing. By default they are set to give the normal spacing, but you can change them with `\setlength` if you wish.

`\cftZtitlefont` The code for typesetting the title of the new listing looks roughly like this

```
\cftafterZtitle
\vspace*{\cftbeforeZtitleskip}
{\cftZtitlefont flist}{\cftafterZtitle}
\cftmarkZ
\vskip \cftafterZtitleskip
```

The default definition of `\cftZtitlefont` is for a bold font. If, for example, you

would prefer the title to be in a large italic font and set flushright you could:
`\renewcommand{\cftZtitlefont}{\hfill\Large\itshape}`
 By default `\cftafterZtitle` is defined to do nothing; you can change it to serve your own purposes. For example:
`\renewcommand{\cftafterZtitle}{\thispagestyle{empty}}`
 will set the page style of the first page of the new listing to be `empty`.

`\newfloatentry` The command `\newfloatentry[⟨within⟩]{⟨counter⟩}{⟨ext⟩}{⟨level-1⟩}` is used internally by `\newfloatlist` to generate a new counter for the new float environment and to generate the typesetting code for entries in the new listing. The required `⟨counter⟩` argument is the name for a new counter. If the optional `⟨within⟩` argument is used, the counter `⟨counter⟩` will be reset each time the counter `⟨within⟩` is changed. These first two arguments have the same effect as calling `\newcounter{⟨counter⟩}[⟨within⟩]`. The `⟨ext⟩` argument is the extension for the file holding the entries, and `⟨level-1⟩` is one less than the ‘level’ of the entry. Continuing the figure example,
`\newfloatlist[chapter]{figure}{lof}{\listfigurename}{\figurename}`
 will internally call
`\newfloatentry[chapter]{figure}{lof}{0}`.

`\newfloatentry` generates a set of commands in addition to those directly generated by `\newfloatlist`. Assuming, as above, that we had
`\newfloatlist{X}{Z}{flist}{fcap}` then we will also have
`\newfloatentry{X}{Z}{0}`. This generates the following.

`X` The counter `X` matches the environment `X`. This counter is used for numbering captions. Remember that it will be reset according to the `⟨within⟩` argument.

`\theX` The command `\theX` prints the value of the `X` counter. It is initially defined so that it prints arabic numerals. If the optional `⟨within⟩` argument is used, `\theX` is defined as
`\renewcommand{\theX}{\thewithin.\arabic{X}}` otherwise as
`\renewcommand{\theX}{\arabic{X}}`.

`\cftbeforeXskip` This length controls the vertical space above a caption entry in the listing. It can be changed by using `\setlength`.

`\cftXindent` The indentation of a caption entry in the listing from the left margin is given by the length `\cftXindent`, and the space for the caption number is set by the length `\cftXnumwidth`. These may be changed via `\setlength` or by `\setnewfloatindents`. The default values for these depend on the value of the `⟨level-1⟩` argument. A value of zero for this sets the defaults to the figure and table values. A value of one sets them to the defaults for subfigure and subtable values.

The code for typesetting a caption entry is roughly like:

```
{\cftXfont {\cftXpresnum SNUM\cftXaftersnum\hfil} \cftXaftersnumb TITLE}%
{\cftXleader}{\cftXpagefont PAGE}\cftXafterpnum\par
```

where `SNUM` is the caption number, `TITLE` is the caption text, and `PAGE` is the page number. The other commands are described below.

`\cftXfont` This controls the appearance of the number and title. By default it is defined

to use the normal font but it can be changed with `\renewcommand`.

`\cftXpresnum` The caption number is typeset in a box of width `\cftXnumwidth`. Within the box, `\cftXpresnum` is first called, then the number is typeset, then `\cftXaftersnum` is called and finally there is a `\hfil` to make the box contents flush left. After the number box is typeset `\cftXaftersnumb` is called and then the caption text is typeset. By default these three macros are defined to do nothing, but `\renewcommand` can be used to make them do something interesting.

`\cftXleader` `\cftXleader` defines the leader between the text and the page number; it can be changed by `\renewcommand`. By default it produces a dotted leader with `\cftXdotsep` space between the dots. Its default definition is `\newcommand{\cftXdotsep}{4.5}` which gives a 4.5mu (math units) separation. In spite of it appearing to be a length, changes to `\cftXdotsep` must be made by `\renewcommand`.

`\cftXpagefont` `\cftXpagefont` specifies the font to be used for typesetting the page number. By default it is set to the normal font. Finally, `\cftXafterpnum` is called after setting the page number; by default it does nothing. Both these commands can be changed by `\renewcommand`.

Note that `\newfloatlist` effectively generates all the above commands. Their defaults are set so that the typesetting mimics that for figure and table captions. It is probable that you can ignore all of them, but if you do want to change something the `tocloft` documentation provides many examples.

`\setnewfloatindents` The command `\setnewfloatindents{<fenv>}{<indent>}{<numwidth>}` sets the `<fenv>`'s entry indent to the length `<indent>` and its numwidth to the length `<numwidth>`. The `<fenv>` argument is the full name of the (sub)float.

As a fuller example of `\newfloatlist`, suppose you wanted both figures (which come with the standard classes), and diagrams. You could then do something like the following.

```
\usepackage{ccaption}
...
\newcommand{\diagramname}{Diagram}
\newcommand{\listdiagramname}{List of Diagrams}
\newfloatlist{diagram}{dgm}{\listdiagramname}{\diagramname}
\newfixedcaption{\fdiagcaption}{diagram}
\begin{document}
...
\listoffigures
\listofdiagram
...
\begin{diagram}
\caption{A diagram} \label{diag1}
...
\end{diagram}
As diagram~\ref{diag1} shows ...
\begin{minipage}{.9\textwidth}
\fdiagcaption{Another diagram} \label{diag2}
...
\end{minipage}
```

In contrast to `diagram~\ref{diag1}`, `diagram~\ref{diag2}` provides ...

As a word of warning, if you mix both floats and fixed environments with the same kind of caption you have to ensure that they get printed in the correct order in the final document. If you do not do this, then the `\list...` of captions will come out in the wrong order (the lists are ordered according the page number in the typeset document, *not* your source input order).

`\newsubfloat` The `\newsubfloat{<fenv>}` command, which is only of use with the `subfigure` package and the `subfigure20` or `subfigure` option, creates subcaptions (`\subtop` and `\subbottom`, together with their continued forms) for use within the float environment `<fenv>` previously defined via `\newfloatlist[...]{<fenv>}{...}`.

The `\newsubfloat` macro internally calls the `\newfloatentry` command and assuming our usual `\newfloatlist{X}{Z}{flist}{fcap}` then `\newsubfloat{X}` calls

`\newfloatentry[X]{subX}{Z}{1}`

so there is a further set of `\cftsubX...` commands generated for adjusting the typesetting of the subcaption entries. Note that the full name of the entry in the listing is ‘sub<fenv>’, not just simply ‘<fenv>’.

`\newfloatpagesoff` The `\newfloatpagesoff{<fenv>}` command will turn off page numbering for list entries for `<fenv>`. This is probably most likely to be used for switching off page numbers for subfloat entries, in which case it should be called as `\newfloatpagesoff{sub<fenv>}`.

`\newfloatpageson` The `\newfloatpageson{<fenv>}` command reverses the effect of a corresponding `\newfloatpagesoff{<fenv>}`.

`\newfloatenv` **NOTE:** These two macros were in version 2.7 of the package but were replaced in version 3.0 by the functionally extended `\newfloatlist` and `\listofX` commands, respectively.

`\listfloats`

There is a limit to the number of List of... listings that (La)TeX can handle. Each kind of listing requires a `\jobname.ext` file and the TeX program has an upper limit on the number of files it can handle. In the most limited circumstance LaTeX requires three files — the `log`, `aux` and `dvi` files. Further files are required for things like a ToC (`toc`) or an index (`idx`). If you try and create too many new listings LaTeX will respond with the error message:

No room for a new write

If you get such a message the only recourse is to redesign your document.

2.8 How LaTeX makes captions

This section provides an overview of how LaTeX creates captions and gives some examples of how to change the captioning style without having to use any package. The section need not be looked at more than once unless you like reading LaTeX code or you want to make changes to LaTeX’s style of captioning.

The LaTeX kernel provides tools to help in the definition of captions, but it is the particular class that decides on their format.

`\caption` The kernel (in `ltfloat.dtx`) defines the caption command via

```
\def\caption{\refstepcounter\@capytype \@dblarg{\@caption\@capytype}}
```

`\@capytype` `\@capytype` is defined by the code that creates a new float environment and is set to the environment's name (see the code for `\@xfloat` in `ltfloat.dtx`). For a `figure` environment, there is an equivalent to

```
\def\@capytype{figure}.
```

`\@caption` The kernel also provides the `\@caption{<type>}[<short-title>]{<full-title>}` command as:

```
\long\def\@caption#1[#2]#3{%
  \par
  \addcontentsline{\csname ext@#1\endcsname}{#1}% <----
  {\protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}}%
  \begingroup
    \@parboxrestore
    \if@minipage
      \@setminipage
    \fi
    \normalsize
    \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par % <----
  \endgroup}
```

where `<type>` is the name of the environment in which the caption will be used. Putting these three commands together results in the user's view of the caption command as `\caption[<short-title>]{<full-title>}`.

It is the responsibility of the class (or package) which defines floats to provide definitions for `\ext@type`, `\fnum@type` and `\@makecaption` which appear in the definition of `\@caption` (in the lines marked <---- above).

`\ext@type` This macro holds the name of the extension for a 'List of...' file. For example for the `figure` float environment there is the definition equivalent to

```
\newcommand{\ext@figure}{lof}.
```

`\fnum@type` This macro is responsible for typesetting the caption number. For example, for the `figure` environment there is the definition equivalent to

```
\newcommand{\fnum@figure}{\figurename~\thefigure}.
```

`\@makecaption` The `\@makecaption{<number>}{<text>}`, where `<number>` is a string such as 'Table 5.3' and `<text>` is the caption text, performs the typesetting of the caption, and is defined in the standard classes (in `classes.dtx`) as the equivalent of:

```
\newcommand{\@makecaption}[2]{%
  \vskip\abovecaptionskip % <- 1
  \sbox\@tempboxa{#1: #2}% % <- 2
  \ifdim \wd\@tempboxa >\hsize
    #1: #2\par % <- 3
  \else
    \global \@minipagefalse
    \hb@xt@\hsize{\hfil\box\@tempboxa\hfil}%
  \fi
  \vskip\belowcaptionskip % <- 4}
```

A THOUSAND WORDS...

FIGURE 4: A picture is worth a thousand words

`\abovecaptionskip` Vertical space is added before and after a caption (lines marked 1 and 4 in the code for `\@makecaption` above) and the amount of space is given by the lengths `\abovecaptionskip` and `\belowcaptionskip`. The standard classes set these to 10pt and 0pt respectively. If you want to change the space before or after a caption, use `\setlength` to change the values. In figures, the caption is usually placed below the illustration. The actual space between the bottom of the illustration and the baseline of the first line of the caption is the `\abovecaptionskip` plus the `\parskip` plus the `\baselineskip`. If the illustration is in a `center` environment then additional space will be added by the `\end{center}`; it is usually better to use the `\centering` command rather than the `center` environment.

The actual typesetting of a caption is effectively performed by the code in lines marked 2 and 3 in the code for `\@makecaption`; note that these are where the colon that is typeset after the number is specified. If you want to make complex changes to the default captioning style you may have to create your own version of `\@caption` using `\renewcommand`. On the other hand, many such changes can be achieved by changing the definition of the the appropriate `\fnum@type` command(s). For example, to make the figure name and number bold:

```
\renewcommand{\fnum@figure}{\textbf{\figurename~\thefigure}}
```

REMEMBER: If you are doing anything involving commands that include the `@` character, and it's not in a class or package file, you have to do it within a `\makeatletter` and `\makeatother` pairing. So, if you modify the `\fnum@figure` command anywhere in your document it has to be done as:

```
\makeatletter
\renewcommand{\fnum@figure}{.....}
\makeatother
```

As an example, Figure 4 was created by the following code:

```
\makeatletter
\renewcommand{\fnum@figure}{\textsc{\figurename~\thefigure}}
\makeatother
\begin{figure}
\centering
A THOUSAND WORDS\ldots
\caption{A picture is worth a thousand words}\label{fig:sc}
\end{figure}
```

As another example, suppose that you needed to typeset the `\figurename` and its number in a bold font, replace the colon that normally appears after the

ANOTHER THOUSAND WORDS...

Figure 5 — A different kind of figure caption

number by a long dash, and typeset the actual title text in a sans-serif font, as is illustrated by the caption for Figure 5. The following code does this.

```
\makeatletter
\renewcommand{\fnum@figure}[1]{\textbf{\figurename~\thefigure} --- \sffamily}
\makeatother
\begin{figure}
  \centering
  ANOTHER THOUSAND WORDS\ldots
\caption{A different kind of figure caption}\label{fig:sf}
\end{figure}
```

Perhaps a little description of how this works is in order. Doing a little bit of TeX's macro processing by hand, the typesetting lines in `\@makecaption` (lines 2 and 3) get instantiated like:

```
\fnum@figure{\figurename~\thefigure}: text
```

Redefining `\fnum@figure` to take one argument and then not using the value of the argument essentially gobbles up the colon. Using

```
\textbf{\figurename~\thefigure}
```

in the definition causes `\figurename` and the number to be typeset in a bold font. After this comes the long dash. Finally, putting `\sffamily` at the end of the redefinition causes any following text (i.e., the actual title) to be typeset using the sans-serif font.

If you do modify `\@makecaption`, then spaces in the definition may be important; also you must use the comment (%) character in the same places as I have done above.

You may also want to take a look at the `caption2` package by Harald Axel Sommerfeldt which provides a ready-made set of differing captioning styles. This basically works by redefining the `\@makecaption` command to provide some hooks. Of course the `ccaption` package provides the tools that you need to make most, if not all, of any likely caption styles.

2.9 Changing the numbering scheme

In the `article` class and its derivatives, captions are numbered continuously throughout the document, while in the `book` and `report` classes, numbering starts anew in each chapter.

If you want captions to be numbered anew with sections in the `article` class you can do this:

```
\makeatletter
\@addtoreset{table}{section}
```

```
\renewcommand{\thetable}{\thesection.\arabic{table}}
\makeatletter
```

and similarly for all the other float environments.

If you are using the `book` or `report` class and you want the captions to be numbered consecutively throughout the document you can do this:

```
\makeatletter
\@removefromreset{table}{chapter}
\renewcommand{\thetable}{\arabic{table}}
\makeatother
```

and similarly for all the other float environments. Note that you will need the `remreset` package¹ which provides the definition of `\@removefromreset`.

You can play with other combinations of `\@addtoreset`, `\@removefromreset`, and `\renewcommand{\the...}{...}` to get the numbering scheme you want.

2.10 Captions with footnotes

If you want to have a caption with a footnote, think long and hard as to whether this is really essential. It is not normally considered to be good typographic practice, and to rub the point in LaTeX does not make it necessarily easy to do. However, if you (or your publisher) insists, read on.

If it is present, the optional argument to `\caption` is put into the LoF/LoT as appropriate. If the argument is not present, then the text of the required argument is put into the LoF. In the first case, the optional argument is moving, and in the second case the required argument is moving. The `\footnote` command is fragile and must be `\protected` (i.e., `\protect\footnote{}`) if it is used in a moving argument. If you don't want the footnote to appear in the LoF, use a footnoteless optional argument and a footnoted required argument.

You will probably be surprised if you just do, for example:

```
\begin{figure}
...
\caption[For LoF]{For figure\footnote{The footnote}}
\end{figure}
```

because (a) the footnote number may be greater than you thought, and (b) the footnote text has vanished. This later is because LaTeX won't typeset footnotes from a float. To get an actual footnote within the float you have to use a minipage, like:

```
\begin{figure}
\begin{minipage}{\linewidth}
...

```

¹Available on CTAN in `tex-archive/macros/latex/contrib/supported/carlise`.

Figure 6 — Float with two illustrations

```

\caption[For LoF]{For figure\footnote{The footnote}}
\end{minipage}
\end{figure}

```

Now you may find that you get two footnotes for the price of one. Fortunately, if you use the `ccaption` package *without* the `caption2` option, this will not occur.

When using a minipage as above, the footnote text is typeset at the bottom of the minipage (i.e., within the float). If you want the footnote text typeset at the bottom of the page, then you have to use the `\footnotemark` and `\footnotetext` commands like:

```

\begin{figure}
...
\caption[For LoF]{For figure\footnotemark}
\end{figure}
\footnotetext{The footnote}

```

This will typeset the argument of the `\footnotetext` command at the bottom of the page where you called the command. Of course, the figure might have floated to a later page, and then it's a matter of some manual fiddling to get everything on the same page, and possibly to get the footnote marks to match correctly with the footnote text.

At this point, you are on your own.

2.11 Multiple floats

As far as LaTeX is concerned, a float is a box which certain restrictions as to where it can be placed. You can effectively put what you like inside a float box. Normally there is just a single picture or tabular in a float but you can put as many of these as will fit inside a float.

Three typical cases of multiple figures/tables in a single float come to mind:

- Multiple illustrations/tabulars with a single caption.
- Multiple illustrations/tabulars each individually captioned.
- Multiple illustrations/tabulars with one main caption and individual sub-captions.

The `subfigure` package is designed for the last of these cases; the others do not require a package.

Figure 6 is an example of multiple illustrations in a single float with a single caption. This figure was produced by the following code.

ILLUSTRATION 3

Figure 7 — Illustration 3

ILLUSTRATION 4

Figure 8 — Illustration 4

```
\begin{figure}
\centering
\hspace*{\fill} {ILLUSTRATION 1} \hfill {ILLUSTRATION 2} \hspace*{\fill}
\caption{Float with two illustrations} \label{fig:mult1}
\end{figure}
```

The `\hspace*{\fill}` and `\hfill` commands were used to space the two illustrations equally. Of course `\includegraphics` or `tabular` environments could just as well be used instead of the `{ILLUSTRATION N}` text.

The following code produces Figures 7 and 8 which are examples of two separately captioned illustrations in one float.

```
\begin{figure}
\centering
\begin{minipage}{0.4\textwidth}
\centering
ILLUSTRATION 3
\caption{Illustration 3} \label{fig:mult2}
\end{minipage}
\hfill
\begin{minipage}{0.4\textwidth}
\centering
ILLUSTRATION 4
\caption{Illustration 4} \label{fig:mult3}
\end{minipage}
\end{figure}
```

In this case the illustrations (or graphics or tabulars) are put into separate `minipage` environments within the float, and the captions are also put within the `minipages`. Note that any required `\label` must also be inside the `minipage`. If you wished, you could add yet another caption after the end of the two `minipages`.

Keith Reckdahl [Rec97] provides more examples of this kind of thing.

2.12 Where LaTeX puts floats

The general format for a float environment is:

`\begin{float}[<loc>] ... \end{float}` or for double column floats:

`\begin{float*}[<loc>] ... \end{float*}`

where the optional argument `<loc>`, consisting of one or more characters, specifies a location where the float may be placed. Note that the `multicol` package only supports the starred floats and it will not let you have a single column float. The possible `<loc>` values are one or more of the following:

- b** *bottom*: at the bottom of a page. This does not apply to double column floats as they may only be placed at the top of a page.
- h** *here*: if possible exactly where the float environment is defined. It does not apply to double column floats.
- p** *page*: on a separate page containing only floats (no text).
- t** *top*: at the top of a page.
- !** make an extra effort to place the float at the earliest place specified by the rest of the argument.

The default for $\langle loc \rangle$ is **tbp**, so the float may be placed at the top, or bottom, or on a float-only page; the default works well 95% of the time. Floats of the same kind are output in definition order, except that a double column float may be output before a later single column float of the same kind, or *vice-versa*². A float is never put on an earlier page than its definition but may be put on the same or later page of its definition. If a float cannot be placed, all succeeding floats will be held up, and LaTeX can store no more than 16 held up floats. A float cannot be placed if it would cause an overfull page, or it otherwise cannot be fitted according to the float parameters. A `\clearpage` or `\cleardoublepage` or `\end{document}` flushes out all unprocessed floats, irrespective of the $\langle loc \rangle$ and float parameters, putting them on float-only pages.

`\suppressfloats`

You can use the command `\suppressfloats[$\langle pos \rangle$]` to suppress floats at a given $\langle pos \rangle$ on the current page. `\suppressfloats[t]` prevents any floats at the top of the page and `\suppressfloats[b]` prevents any floats at the bottom of the page. The simple `\suppressfloats` prevents both top and bottom floats.

The `flafter` package, which should have come with your LaTeX distribution, provides a means of preventing floats from moving backwards from their definition position in the text. This can be useful to ensure, for example, that a float early in a `\section{}` is not typeset before the section heading.

Table 4 lists the various float parameters and typical default values. All the lengths are rubber lengths, and the actual defaults depend on both the class and its size option.

Given the displayed defaults, the height of a top float must be less than 70% of the `textheight` and there can be no more than 2 top floats on a text page. Similarly, the height of a bottom float must not exceed 30% of the `textheight` and there can be no more than 1 bottom float on a text page. There can be no more than 3 floats (top, bottom and here) on the page. At least 20% of a text page with floats must be text. On a float page (one that has no text, only floats) the sum of the heights of the floats must be at least 50% of the `textheight`. The floats on a float page should be vertically centered.

It can be seen that with the defaults LaTeX might have trouble finding a place for a float. Consider what will happen if a float is a bottom float whose height is

²This little quirk is fixed by the `fixltx2e` package, at least for tables and figures. The package is part of a normal LaTeX distribution.

Table 4: Float placement parameters

Parameter	Controls	Default
Counters — change with <code>\setcounter</code>		
<code>topnumber</code>	max number of floats at top of a page	2
<code>bottomnumber</code>	max number of floats at bottom of a page	1
<code>totalnumber</code>	max number of floats on a text page	3
<code>dbltopnumber</code>	like <code>topnumber</code> for double column floats	2
Commands — change with <code>\renewcommand</code>		
<code>\topfraction</code>	max fraction of page reserved for top floats	0.7
<code>\bottomfraction</code>	max fraction of page reserved for bottom floats	0.3
<code>\textfraction</code>	min fraction of page that must have text	0.2
<code>\dbltopfraction</code>	like <code>\topfraction</code> for double column floats	0.7
<code>\floatpagefraction</code>	min fraction of a float page that must have float(s)	0.5
<code>\dblfloatpagefraction</code>	like <code>\floatpagefraction</code> for double column floats	0.5
Text page lengths — change with <code>\setlength</code>		
<code>\floatsep</code>	vertical space between floats	12pt
<code>\textfloatsep</code>	vertical space between a top (bottom) float and succeeding (preceeding) text	20pt
<code>\intextsep</code>	vertical space above and below an h float	12pt
<code>\dblfloatsep</code>	like <code>\floatsep</code> for double column floats	12pt
<code>\dbltextfloatsep</code>	like <code>\textfloatsep</code> for double column floats	20pt
Float page lengths — change with <code>\setlength</code>		
<code>\@fptop</code>	space at the top of the page	0pt plus 1fil
<code>\@fpsep</code>	space between floats	8pt plus 2fil
<code>\@fpbot</code>	space at the bottom of the page	0pt plus 1fil
<code>\@dblfp top</code>	like <code>\@fptop</code> for double column floats	0pt plus 1fil
<code>\@dblfp sep</code>	like <code>\@fpsep</code> for double column floats	8pt plus 2fil
<code>\@dblfp bot</code>	like <code>\@fpbot</code> for double column floats	0pt plus 1fil

40% of the `textheight` and this is followed by a float whose height is 90% of the `textheight`. The first is too large to actually go at the bottom of a text page but too small to go on a float page by itself. The second has to go on a float page but it is too large to share the float page with the first float. LaTeX is stuck!

At this point it is worthwhile to be precise about the effect of a one character `<loc>` argument:

- [b] means: ‘put the float at the bottom of a page with some text above it, and nowhere else’. The float must fit into the `\bottomfraction` space otherwise it and subsequent floats will be held up.
- [h] means: ‘put the float at this point and nowhere else’. The float must fit into the space left on the page otherwise it and subsequent floats will be held up.
- [p] means: ‘put the float on a page that has no text but may have other floats on it’. There must be at least ‘`\floatpagefraction`’ worth of floats to go on a float only page before the float will be output.
- [t] means: ‘put the float at the top of a page with some text below it, and nowhere else’. The float must fit into the `\topfraction` space otherwise it and subsequent floats will be held up.

[!...] means: ‘ignore the `\...fraction` values for this float’.

You must try and pick a combination from these that will let LaTeX find a place to put your floats. However, you can also change the float parameters to make it easier to find places to put floats. Some examples are:

- Decrease `\textfraction` to get more ‘float’ on a text page, but the sum of `\textfraction` and `\topfraction` and the sum of `\textfraction` and `\bottomfraction` should not exceed 1, otherwise the placement algorithm falls apart. A minimum value for `\textfraction` is about 0.10 — a page with less than 10% text looks better with no text at all, just floats.
- Both `\topfraction` and `\bottomfraction` can be increased, and it does not matter if their sum exceeds 1.0. A good typographic style is that floats are encouraged to go at the top of a page, and a better balance is achieved if the float space on a page is larger at the top than the bottom.
- Making `\floatpagefraction` too small might have the effect of a float page just having one small float. However, to make sure that a float page never has more than one float on it, do:

```
\renewcommand{\floatpagefraction}{0.01}
\setlength{\@fpsep}{\textheight}
```
- Setting `\@fptop` to 0pt, `\@fpsep` to 8pt and `\@fpbot` to 0pt plus 1fil will force floats on a float page to start at the top of the page.

If you are experimenting, a reasonable starting position is:

```
\setcounter{topnumber}{3}
\setcounter{bottomnumber}{2}
\setcounter{totalnumber}{4}
\renewcommand{\topfraction}{0.85}
\renewcommand{\bottomfraction}{0.5}
\renewcommand{\textfraction}{0.15}
\renewcommand{\floatpagefraction}{0.7}
```

and similarly for double column floats if you will have any.

One of LaTeX's little quirks is that on a text page, the 'height' of a float is its actual height plus `\textfloatsep` or `\floatsep`, while on a float page the 'height' is the actual height. This means that when using the default *loc* of `[tbp]` at least one of the text page float fractions (`\topfraction` and/or `\bottomfraction`) must be larger than the `\floatpagefraction` by an amount sufficient to take account of the maximum text page separation value.

3 The package code

Announce the name and version of the package, which requires LaTeX2e.

```
1 \*usc)
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{ccaption}[2002/10/18 v3.1b Extended captioning and new floats]
4
```

In an attempt to avoid name clashes with other packages, all internal commands include the string `@cont`.

Note (2001/08/03): Older versions of the `amsmath` package did odd things with `\@tempa`, `\@tempb` and `\@tempc`. I have replaced any original use of these by `\@conttempa`, etc.

Do the options first.

```
\if@contsubfigxx These three \if... are used to remember if the subfigure20 or subfigure option
\if@contsubfigxxi has been given.
  \if@contsubfig
    5 \newif\if@contsubfigxx
    6   \@contsubfigxxfalse
    7 \newif\if@contsubfigxxi
    8   \@contsubfigxxifalse
    9 \newif\if@contsubfig
    10   \@contsubfigfalse
    11 \DeclareOption{subfigure20}{\@contsubfigxxtrue\@contsubfigxxifalse\@contsubfigtrue}
    12 \DeclareOption{subfigure21}{\@contsubfigxxfalse\@contsubfigxxitruetrue\@contsubfigtrue}
    13 \PackageWarningNoLine{ccaption}{%
    14   The subfigure21 option is deprecated.\MessageBreak
    15   Try and use the subfigure option instead}}
    16 \DeclareOption{subfigure}{\@contsubfigxxfalse\@contsubfigxxitruetrue\@contsubfigtrue}
```

`\if@contcaption` This `\if...` is used to remember if the `caption2` option has been given

```

17 \newif\if@contcaption
18   \@contcaptionfalse
19 \DeclareOption{caption2}{\@contcaptiontrue}

```

`\if@conttitleopt` This `\if...` is used to remember if the `titles` option has been given

```

20 \newif\if@conttitleopt
21   \@conttitleoptfalse
22 \DeclareOption{titles}{\@conttitleopttrue}

```

`\ProcessOptions` Now process the options.

```

23
24 \ProcessOptions\relax
25

```

3.1 Caption styling

The caption styling³ is accomplished by redefining the `\@makecaption` command. First, though, define and initialise the user-level commands.

The styling is only defined if the `caption2` option is *not* given. But first we have to declare some new `\if` commands before testing the option.

```

\if@contcw For use when checking caption width and captioning styles styles.
\if@conthang 26 \newif\if@contcw
\if@contindent 27 \newif\if@conthang
                28 \newif\if@contindent
                29

                Issue a warning if the caption2 option has been used.
                30 \if@contcaption
                31   \PackageWarningNoLine{ccaption}}%
                32     {You have used the caption2 option.\MessageBreak
                33       The ccaption styling commands\MessageBreak
                34       are unavailable to you}
                35 \else
                36
\captiondelim For the caption delimiter.
\@contdelim 37 \newcommand{\captiondelim}[1]{\def\@contdelim{#1}}
              38 \captiondelim{: }
              39

\captionnamefont The font for the caption name.
\@contnfont 40 \newcommand{\captionnamefont}[1]{\def\@contnfont{#1}}
              41 \captionnamefont{}
              42

```

³Thanks to Donald Arseneau and Arash Esbatil for their perceptive comments on early versions of the styling code.

<code>\captiontitlefont</code>	The font for the caption title.
<code>\@conttfont</code>	43 <code>\newcommand{\captiontitlefont}[1]{\def\@conttfont{#1}}</code>
	44 <code>\captiontitlefont{}</code>
	45
<code>\flushleftrighth</code>	These are in addition to the <code>\centering</code> , <code>\raggedleft</code> and <code>\raggedright</code> declarations for paragraphing. <code>\flushleftrighth</code> sets the skips to TeX's normal (block) paragraphing values, while <code>\centerlastline</code> sets the skips to give a centered last line in a block paragraph.
<code>\centerlastline</code>	
	46 <code>\newcommand{\flushleftrighth}{%</code>
	47 <code>\leftskip\z@ \rightskip\z@</code>
	48 <code>\parfillskip=\z@ plus 1fil}</code>
	49 <code>\newcommand{\centerlastline}{%</code>
	50 <code>\leftskip=\z@ plus 1fil</code>
	51 <code>\rightskip=\z@ plus -1fil</code>
	52 <code>\parfillskip=\z@ plus 2fil}</code>
	53
<code>\captionstyle</code>	The paragraphing style for the caption.
<code>\@contcstyle</code>	54 <code>\newcommand{\captionstyle}[1]{\def\@contcstyle{#1}}</code>
	55 <code>\captionstyle{}</code>
	56
<code>\@contcwidth</code>	The macros for dealing with the caption width.
<code>\captionwidth</code>	57 <code>\newlength{\@contcwidth}</code>
<code>\changepcaptionwidth</code>	58 <code>\newcommand{\captionwidth}[1]{\setlength{\@contcwidth}{#1}}</code>
<code>\normalcaptionwidth</code>	59 <code>\captionwidth{\linewidth}</code>
	60 <code>\newcommand{\changepcaptionwidth}{\@contcwtrue}</code>
	61 <code>\newcommand{\normalcaptionwidth}{\@contcwfalse}</code>
	62 <code>\normalcaptionwidth</code>
	63
<code>\@contindw</code>	The macros for hanging and indented captions.
<code>\hangcaption</code>	64 <code>\newlength{\@contindw}</code>
<code>\indentcaption</code>	65 <code>\newcommand{\hangcaption}{\@conthangtrue\@contindentfalse}</code>
<code>\normalcaption</code>	66 <code>\newcommand{\indentcaption}[1]{\setlength{\@contindw}{#1}%</code>
	67 <code>\@conthangfalse\@contindenttrue}</code>
	68 <code>\newcommand{\normalcaption}{\@conthangfalse\@contindentfalse}</code>
	69 <code>\normalcaption</code>
	70
<code>\precaption</code>	The macros for the pre- and post-caption text/commands, and for the mid-caption command for bilingual captions.
<code>\@contpre</code>	
<code>\postcaption</code>	71 <code>\newcommand{\precaption}[1]{\def\@contpre{#1}}</code>
<code>\@contpost</code>	72 <code>\precaption{}</code>
<code>\midbication</code>	73 <code>\newcommand{\postcaption}[1]{\def\@contpost{#1}}</code>
<code>\@contmidbi</code>	74 <code>\postcaption{}</code>
	75 <code>\newcommand{\midbication}[1]{\def\@contmidbi{#1}}</code>
	76 <code>\midbication{}</code>
	77

`\@makecaption` This is a reimplementation of the kernel `\@makecaption` command. As well as including the caption typesetting commands it enables captions that include forced newlines (e.g., by `\`).

The first part is due to Donald Arseneau⁴ from postings to the CTT newsgroup and Email discussions. The `\topskip` strut is used whenever the caption is the first part of the float. This means, among other things, that if a caption comes at the top of a page, then the first line of the caption will be aligned with the normal first line of a page. The `\abovecaptionskip` is only used when there is something above the caption in the current float.

```
78 \long\def\@makecaption#1#2{\let\@conttempa\relax
79 \ifdim\prevdepth>-99\p@ \vskip\abovecaptionskip
80 \else \def\@conttempa{\vbox to\topskip{}}\fi
```

`\@contfnote` The caption title will be typeset twice, firstly to measure its width and secondly to
`\@contfmark` actually typeset it. To avoid problems caused by a footnote in the caption getting processed twice, we temporarily disable the expected relevant commands.

```
81 \let\@contfnote\footnote \renewcommand{\footnote}[2] [] {}
82 \let\@contfmark\footnotemark \renewcommand{\footnotemark}[1] [] {}
83 \let\@contlabel\label \renewcommand{\label}[1] {}
```

Now measure the width of the total caption, not forgetting to take account of the font specifications, and then restore the footnoting.

```
84 \sbox\@tempboxa{\@contnfont #1\@contdelim \@conttfont #2}
85 \let\footnote\@contfnote
86 \let\footnotemark\@contfmark
87 \let\label\@contlabel
```

If the caption is less than one line, then the whole caption needs to be centered on the page (otherwise the short caption may be typeset flushleft).

```
88 \ifdim\wd\@tempboxa<\linewidth \centering \fi
89 \if@contcw
```

For typesetting at anything other than the normal width, put the caption into a `\parbox` of the specified width. This must be centered.

```
90 \centering
91 \parbox{\@contcwidth}{%
92 \fi
93 \if@conthang
```

For a hanging caption we have to measure the width of the caption name, then typeset the whole caption in a hanging paragraph.

```
94 \sbox\@tempboxa{\@contnfont #1\@contdelim}
95 \@contpre%
96 {\@contnfont #1\@contdelim}\@conttempa
97 {\@contcstyle\hangindent=\wd\@tempboxa\hangafter=\@one\@conttfont #2\par}
98 \else
99 \if@contindent
```

⁴Email: asnd@triumf.ca

An indented caption is similar, except the amount of indentation is kept in `\@contindw`.

```

100     \@contpre%
101     {\@contnfont #1\@contdelim}\@conttempa
102     {\@contcstyle\hangindent=\@contindw\hangafter=\@ne\@conttfont #2\par}
103     \else

```

For the normal style, just typeset the caption.

```

104     \@contpre%
105     {\@contnfont #1\@contdelim}\@conttempa
106     {\@contcstyle\@conttfont #2\par}
107     \fi
108     \fi

```

Finish off the typesetting by processing the post-text, and if not using the normal width then close off the `\parbox`, and lastly put in some vertical space.

```

109     \@contpost
110     \if@contcw
111         \par
112     } % end of parbox
113     \fi
114     \vskip\belowcaptionskip}
115

```

This finishes off the non `caption2` option.

```

116 \fi % end of test (\if@contcapoption) on caption2 option
117

```

3.2 Continuation captions and legends

`\contcaption` `\contcaption{<text>}` is a user-level command. It is a simplified version of the normal `\caption` command as it doesn't have to deal too much with numbering or list of ... entries.

```

118 \newcommand{\contcaption}{%
119     \addtocounter{\@capttype}{\m@ne}%
120     \refstepcounter{\@capttype}%
121     \@contcaption\@capttype}
122

```

`\@contcaption` This is the workhorse for the `\contcaption` command. In turn, it uses the `\@makecaption` command (defined in the usual classes) to do most of its work. It uses the number of the previous `\caption` command in the same type of float and its implementation includes much of the code used in the LaTeX `\caption` command.

```

123 \long\def\@contcaption#1#2{%
124     \par
125     \begingroup
126         \@parboxrestore
127         \if@minipage

```

```

128      \@setminipage
129      \fi
130      \normalsize
131      \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #2}\par
132 \endgroup}
133
\abovelegendskip These two lengths control the vertical spacing before and after a legend. We will
\belowlegendskip give these values such that a legend will occupy an integral number of lines.
134 \newlength{\abovelegendskip}
135 \setlength{\abovelegendskip}{0.5\baselineskip}
136 \newlength{\belowlegendskip}
137 \setlength{\belowlegendskip}{\abovelegendskip}
138
\legend The command is called as \legend{<text>}. It is intended to be used in a float
environment for an ‘anonymous’ caption, but can be used anywhere.
The implementation is similar to the \caption command but we have to elim-
inate printing of a delimiter.
139 \newcommand{\legend}[1]{%
140   \par
141   \begingroup
142     \@parboxrestore
143     \if@minipage
144       \@setminipage
145     \fi
146     \normalsize
147     \captiondelim{\mbox{}}
148     \@makecaption{}{\ignorespaces #1}\par
149   \endgroup}
150
\namedlegend \namedlegend[<short-title>]{<long-title>} is like the \caption command except
that it does not number the caption.
151 \newcommand{\namedlegend}{\@dblarg{\@legend\@capttype}}
152
\@legend \@legend{<type>}[<short-title>]{<long-title>} is the workhorse for the \namedlegend
command. In turn, it calls \@makelegend. It requires two commands to
have been defined, namely \flegtoc@type and \fleg@type. The command
\flegtoc@type{<text>} is responsible for writing a title text to the appropriate
listof file. \fleg@type is responsible for typesetting the name of the legend.
153 \long\def\@legend#1[#2]#3{%
154   \par
155   \csname flegtoc@#1\endcsname{#2}%
156   \begingroup
157     \@parboxrestore
158     \if@minipage

```

```

159     \@setminipage
160     \fi
161     \normalsize
162     \@makecaption{\csname fleg@#1\endcsname}{\ignorespaces #3}\par
163 \endgroup}
164

```

`\flegtoc@table` These macros write a `\namedlegend` title to the respective listof file. By default they do nothing.

```

165 \newcommand{\flegtoc@table}[1]{}
166 \newcommand{\flegtoc@figure}[1]{}
167

```

`\fleg@table` These macros typeset the name before the title of a `\namedlegend`. By default they are defined to mimic the normal captioning style.

```

168 \newcommand{\fleg@table}{\tablename}
169 \newcommand{\fleg@figure}{\figurename}
170

```

3.3 Non-float captions

`\newfixedcaption` These commands are defined in terms of their `\...command` counterparts.
`\renewfixedcaption` Call as `\...fixedcaption[<capcommand>]{<command>}{<env>}`
`\providfixedcaption` 171 `\newcommand{\newfixedcaption}[3][\caption]{%`
172 `\newcommand{#2}{\def\@capttype{#3}#1}}`
173 `\newcommand{\renewfixedcaption}[3][\caption]{%`
174 `\renewcommand{#2}{\def\@capttype{#3}#1}}`
175 `\newcommand{\providfixedcaption}[3][\caption]{%`
176 `\providecommand{#2}{\def\@capttype{#3}#1}}`
177

3.4 Bilingual captions

The bilingual caption commands all use internal grouping so that any changes are kept local. This has the unfortunate side-effect that any `\label` command must be within the grouping otherwise the wrong number is picked up. To make the coding, if not necessarily the use, of the commands simpler, I have not used the traditional style of square brackets for optional caption text arguments. Instead, empty ‘required’ arguments are used as the implementation means.

`\@if@contemptyarg` For dealing with empty arguments. `\@if@contemptyarg{<testarg>}{<YES>}{<NO>}` checks if *<testarg>* is empty (consists of zero or more spaces only). If it is empty then the *<YES>* argument is processed otherwise the *<NO>* argument is processed. The implementation uses code suggested by Donald Arseneau (see section A for some background on this).

```

178 \begingroup
179 \catcode'\Q=3
180 \long\gdef\@if@contemptyarg#1{\@xif@contmt#1QQ\@secondoftwo\@firstoftwo\@nil}

```

```

181 \long\gdef\xif@contmt#1#2Q#3#4#5\@nil{#4}
182 \endgroup
183
\bitwonomcaption The 6 arguments are: optional label, short and long in language 1, name in lan-
                   guage 2, and short and long in language 2. Both texts are put into the List of as
                   numbered entries.
184 \newcommand{\bitwonomcaption}[6][\@empty]{%
185   \begingroup
                   Check if the first language argument is vacuous, then call the normal \caption
                   for language 1.
186   \if@contemptyarg{#2}{\caption{#3}}{\caption[#2]{#3}}
                   Do the optional labeling.
187   \ifx #1\@empty\else
188     \label{#1}
189   \fi
                   Remove any extra spacing between the captions, and set the NAME for the second
                   caption. Use a command to transfer the NAME to the renewell code to avoid
                   circularity if for example, we are trying to redefine \tablename as \tablename.
                   Decrement the caption counter.
190   \setlength{\abovecaptionskip}{0pt}
191   \setlength{\belowcaptionskip}{0pt}
192   \edef\@conttempc{#4}
193   \expandafter \renewcommand \csname \@capytype name\endcsname{\@conttempc}
194   \addtocounter{\@capytype}{-1}
                   Now repeat for the second language caption.
195   \@contmidbi
196   \if@contemptyarg{#5}{\caption{#6}}{\caption[#5]{#6}}
197   \endgroup
198 }
199
\bionenumcaption The 6 arguments are: optional labelling, short and long in language 1, name in
                  language 2, and short and long in language 2. Both texts are put into the List of,
                  but only the first is numbered.
200 \newcommand{\bionenumcaption}[6][\@empty]{%
201   \begingroup
                   Check if the first language argument is vacuous, then call the normal \caption
                   for language 1.
202   \if@contemptyarg{#2}{\caption{#3}}{\caption[#2]{#3}}
                   Do the optional labeling.
203   \ifx #1\@empty\else
204     \label{#1}
205   \fi

```

Do the between captions code.

```

206 \setlength{\abovecaptionskip}{0pt}
207 \setlength{\belowcaptionskip}{0pt}
208 \edef\@conttempc{#4}
209 \expandafter \renewcommand \csname \@captype name\endcsname{\@conttempc}

Use a continuation caption for the second language, not forgetting to add the
appropriate unnumbered text to the List.

210 \@contmidbi
211 \contcaption{#6}
212 \if@contemptyarg{#5}{%
213   \addcontentsline{\csname ext@\@captype\endcsname}{\@captype}%
214     {\protect\numberline}{\ignorespaces #6}}{%
215   \addcontentsline{\csname ext@\@captype\endcsname}{\@captype}%
216     {\protect\numberline}{\ignorespaces #5}}
217 \endgroup
218 }
219

```

\bicapcaption The 5 arguments are: optional labelling, short and long in language 1, name in language 2, and long in language 2. Only the first text is put into the List.

```

220 \newcommand{\bicaption}[5][\@empty]{%
221   \begingroup

Check if the first language argument is vacuous, then call the normal \caption
for language 1.

222   \if@contemptyarg{#2}{\caption{#3}}{\caption[#2]{#3}}

Do the optional labeling.

223   \ifx #1\@empty\else
224     \label{#1}
225   \fi

Do the between captions code and finally just use \contcaption for the second
language.

226   \setlength{\abovecaptionskip}{0pt}
227   \setlength{\belowcaptionskip}{0pt}
228   \edef\@conttempc{#4}
229   \expandafter \renewcommand \csname \@captype name\endcsname{\@conttempc}
230   \@contmidbi
231   \contcaption{#5}
232   \endgroup
233 }
234

```

\bicontcaption The 3 arguments are long in language 1, name in language 2, and long in language 2.

```

235 \newcommand{\bicontcaption}[3]{%
236   \begingroup

```

Call `\contcaption` for language 1.

```

237 \contcaption{#1}
    Do the between captions code and use \contcaption for the second language.
238 \setlength{\abovecaptionskip}{0pt}
239 \setlength{\belowcaptionskip}{0pt}
240 \edef\@conttempc{#2}
241 \expandafter \renewcommand \csname \@captype name\endcsname{\@conttempc}
242 \@contmidbi
243 \contcaption{#3}
244 \endgroup
245 }
246

```

3.5 The subfigure options

`\@contkeep` These are common to both subfigure options. `\@contkeep` stores the current subfigure/table number in counter `@contsubnum` and `\@contset` sets the subfigure/table number to the value of `@contsubnum`. `\subconcluded` sets the subfigure/table number to zero. The original definition of `\@contcaption` is kept in `\subfigold@contcaption`.

```

247 \if@contsubfig
248 \newcounter{@contsubnum}
249 \newcommand{\@contkeep}{\setcounter{@contsubnum}{\value{sub\@captype}}}
250 \newcommand{\@contset}{\setcounter{sub\@captype}{\value{@contsubnum}}}
251 \newcommand{\subconcluded}{\setcounter{sub\@captype}{0}}
252 \let\subfigold@contcaption\@contcaption

```

`\toclevel@subtable` These are needed if the `hyperref` package is loaded as well as subfigures.

```

\toclevel@subfigure 253 \providecommand{\toclevel@subtable}{1}
254 \providecommand{\toclevel@subfigure}{1}
255 \fi

```

`\if@contmaincaption` This is set TRUE after the (cont)caption in a float has been processed. (A `\newif` cannot be used within an `\if... \fi` construct.)

```

256 \newif\if@contmaincaption
257 \@contmaincaptionfalse

```

`\if@contbotsub` A flag indicating whether the subcaption is to be at the bottom or top of the subfigure/subtable; TRUE for the subcaption at the bottom.

```

258 \newif\if@contbotsub
259 \@contbotsubtrue
260

```

3.5.1 Option `subfigure20`

In order to eliminate an ordering dependency between the `subfigure` and `ccaption` packages, modifications to the original `subfigure` code have to be done at the start

of the document after all packages have been loaded. First for subfigure 2.0, if it is called for.

```
261 \AtBeginDocument{%
262 \if@contsubfigxx
```

\caption These original commands are all modified to set the value of \if@contmaincaption.
\contcaption The (cont)caption commands set it to TRUE and the float commands set it
\@float FALSE. Additionally, the \@float and \@dbflt commands are modified to zero
\@dbflt the subfloat counter, if it is defined.

```
263 \let\@contoldc\caption
264 \renewcommand{\caption}{\@contmaincaptiontrue\@contoldc}
265 \let\@contoldcont\contcaption
266 \renewcommand{\contcaption}{\@contmaincaptiontrue\@contoldcont}
267 \let\@contoldf\@float
268 \renewcommand{\@float}[1]{\@contmaincaptionfalse
269 \ifundefined{c@sub#1}{\csname c@sub#1\endcsname = 0\relax}
270 \@contoldf{#1}}
271 \let\@contoldff\@dbflt
272 \renewcommand{\@dbflt}[1]{\@contmaincaptionfalse
273 \ifundefined{c@sub#1}{\csname c@sub#1\endcsname = 0\relax}
274 \@contoldff{#1}}
275
```

\@subfloat This macro from subfigure v2.0 is modified to enable subcaptions to be placed at either the top or bottom of the sub... (the original only placed them at the bottom). First, the subfigure/table is set in a box.

```
276 \def\@subfloat#1[#2]#3{%
277 \setbox\@tempboxa \hbox{#3}%
278 \@tempdima=\wd\@tempboxa
279 \if@contbotsub
```

The subcaption is to be put at the bottom, so typeset the figure, followed by the caption, if any.

```
280 \vtop{%
281 \vbox{\vskip\subfigtopskip
282 \box\@tempboxa}%
283 \ifx \@empty#2\relax \else
284 \vskip\subfigcapskip
285 \@subcaption{#1}{#2}%
286 \fi
287 \vskip\subfigbottomskip}%
288 \else
```

The subcaption is to be put at the top, so typeset the caption if any, followed by the figure.

```
289 \vtop{%
290 \ifx \@empty#2\relax \else
291 \vskip\subfigcapskip
292 \begingroup\@subcaption{#1}{#2}\endgroup%
```

```

293         \fi
294         \vbox{\vskip\subfigtopskip
295               \box\@tempboxa}%
296         \vskip\subfigbottomskip}%
297     \fi
298     \egroup}
299

```

`\@subcaption` The original `\@subcaption` command produces unexpected results in the ToC (i.e., `numberline` appears instead of `\numberline` because of the original internal definition of `\protect`). I have also modified it so that when a top main caption is being used, it adds the subcaption to the ToC directly.

Sebastien Derriere found that there were problems when fragile commands were used within a continued subcaption. Steven Douglas Cochran kindly provided a fix for this.

```

300 \renewcommand{\@subcaption}[2]{%
301   \begingroup
302     \let\label\@gobble
303     \let\protect\string      % SDC mod
304     \if@contmaincaption
305       \addcontentsline{\csname ext@#1\endcsname}{#1}%
306         {\protect\numberline{\csname p@#1\endcsname\csname the#1\endcsname}%
307          {\ignorespaces #2}}%
308       \gdef\@subfigcaptionlist{}
309     \else
310       \xdef\@subfigcaptionlist{%
311         \@subfigcaptionlist,%
312 %\string\numberline {\@currentlabel}%    % SDC mod
313         {\protect\numberline {\@currentlabel}%    % SDC mod
314          \noexpand{\ignorespaces #2}}}%
315     \fi
316   \endgroup
317   \@nameuse{@make#1caption}{\@nameuse{@the#1}}{#2}}
318

```

`\subfigure` These are revised versions of the original commands. They are now aliases for `\subtable` `\subbottom` and `\subtop` respectively. In their original form they were both effectively aliases for `\subbottom` only.

```

319 \let\subfigure\subbottom
320 \let\subtable\subtop
321 \fi
322 }

```

The end of the `\AtBeginDocument` code for `subfigure20`.

Do the remaining code for the `subfigure20` option, if called for.

```

323 \if@contsubfigxx

```

`\subbottom` `\subbottom[<caption>]{<text>}` typesets a subcaption when the main caption is at the end of the float environment. The code is a slight modification of the original

`\subfigure` command in that the bottom flag is added and set to true and the subcaption number is stored. The caption number must be locally advanced if the main caption has not yet been processed (i.e., is at the bottom of the float). As most of the code is common with `\subtop` it is placed into the `\@contsubbody` macro.

```

324 \newcommand{\subbottom}{%
325   \@contbotsubtrue
326   \@contsubbody}
327
328 \newcommand{\@contsubbody}{%
329   \bgroup
330   \if@contmaincaption\else
331     \advance\csname c@\@capttype\endcsname\@ne
332   \fi
333   \refstepcounter{sub\@capttype}\@contkeep%
334   \leavevmode
335   \@ifnextchar [%
336     {\@subfloat{sub\@capttype}}
337     {\@subfloat{sub\@capttype}[\@empty]}}
338
```

`\contsubbottom` The continued version of `\subbottom`. It restores the kept subcaption number before incrementing and keeping it. As most of the code is common with `\contsubtop` it is kept in the `\subbody@cont`.

```

339 \newcommand{\contsubbottom}{%
340   \@contbotsubtrue
341   \subbody@cont}
342
343 \newcommand{\subbody@cont}{%
344   \bgroup
345   \@contset
346   \refstepcounter{sub\@capttype}\@contkeep%
347   \leavevmode
348   \@ifnextchar [%
349     {\@subfloat{sub\@capttype}}
350     {\@subfloat{sub\@capttype}[\@empty]}}
351
```

`\subtop` `\subtop[<caption>]{<text>}` typesets a subcaption at the top of the subfigure/table. This is almost identical to `\subbottom`.

```

352 \newcommand{\subtop}{%
353   \@contbotsubfalse
354   \@contsubbody}
355
```

`\contsubtop` The continued version of `\subtop`.

```

356 \newcommand{\contsubtop}{%
357   \@contbotsubfalse
358   \subbody@cont}

```

359

`\@contcaption` The `\@contcaption` command must be modified to add the listed subcaptions (if any, and there should be none for top main captions) to the ToC. A simplified version of the subfigure redefinition of `\@caption`.

```
360 \long\def\@contcaption#1#2{%
361   \subfigold@contcaption{#1}{#2}%
362   \@for \@conttempa:=\@subfigcaptionlist \do {%
363     \ifx\@empty\@conttempa\relax \else
364       \addcontentsline
365         {\@nameuse{ext@sub#1}}%
366         {sub#1}%
367         {\@conttempa}%
368     \fi}%
369   \gdef\@subfigcaptionlist{}}
370
```

`\contsubtable` Aliases for `\contsubtop` and `\contsubbottom`, respectively.

```
\contsubfigure 371 \let\contsubtable\contsubtop
372 \let\contsubfigure\contsubbottom
373
```

The end of the subfigure20 option code.

```
374 \fi
375
```

This is the end of the version 2.0 code.

3.5.2 Option subfigure21

`\caption` These original commands are all modified to set the value of `\if@contmaincaption`.
`\contcaption` The (cont)caption commands set it to TRUE and the float commands set it
`\@float` FALSE. Additionally, the `\@float` and `\@dbflt` commands are modified to zero
`\@dbflt` the subfloat counter, if it is defined.

```
376 \if@contsubfigxxi
377   \let\@contoldc\caption
378   \renewcommand{\caption}{\@contmaincaptiontrue\@contoldc}
379   \let\@contoldcont\contcaption
380   \renewcommand{\contcaption}{\@contmaincaptiontrue\@contoldcont}
381   \let\@contoldf\@float
382   \renewcommand{\@float}[1]{\@contmaincaptionfalse
383     \ifundefined{c@sub#1}{\csname c@sub#1\endcsname = 0\relax}
384     \@contoldf{#1}}
385   \let\@contoldff\@dbflt
386   \renewcommand{\@dbflt}[1]{\@contmaincaptionfalse
387     \ifundefined{c@sub#1}{\csname c@sub#1\endcsname = 0\relax}
388     \@contoldff{#1}}
389 \fi
390
```

`\@contsubfloat` This is a version of the subfigure `\subfigure` command. The revised version stores the subcounter.

```

391 \newcommand{\@contsubfloat}{%
392   \bgroup
393   \let\subfig@oldlabel=\label
394   \let\label=\sub@label
395   \refstepcounter{sub\@capttype}\@contkeep%    % <- change here
396   \ifnextchar [%
397     {\@cont@subfloat}%
398     {\@cont@subfloat[\@empty]}}
399

```

`\@@contsubfloat` This is a revised version of the subfigure `\@subfigure` command (just the called macronames are changed).

```

400 \def\@@contsubfloat[#1]{%
401   \ifnextchar [%
402     {\@@contsubfloat{sub\@capttype}[#1]}%
403     {\@@contsubfloat{sub\@capttype}[\@empty #1][#1]}}
404

```

`\@@@contsubfloat` This is a modified version of the subfigure `\@subfloat` command. Essentially the `\csname if#1topcap\endcsname` constructs are replaced by `\if@contbotsub`. This is actually only required for user-defined floats where I haven't been able to work out if it is possible to create new `\if#1...` commands within a command that has a parameter `#1`.

```

405 \long\def\@@@contsubfloat#1[#2][#3]#4{%
406   \@tempcnta=\@ne
407   \ifsf@tight
408     \if@minipage
409       \@tempcnta=\z@
410     \else
411       \ifdim\lastskip=\z@
412         \@tempcnta=\@ne
413       \else
414         \@tempcnta=\tw@
415       \fi
416     \fi
417   \fi
418   \if@contbotsub
419     \def\subfig@top{\subfigtopskip}%
420     \def\subfig@bottom{\subfigbottomskip}%
421   \else
422     \def\subfig@top{\subfigbottomskip}%
423     \def\subfig@bottom{\subfigtopskip}%
424   \fi
425   \setbox\@tempboxa \hbox{#4}%
426   \@tempdima=\wd\@tempboxa
427   \vtop\bgroup
428     \vbox\bgroup

```

```

429 \ifcase\@tempcnta
430 \@minipagefalse
431 \or
432 \vspace{\subfig@top}
433 \or
434 \ifdim \lastskip=\z@ \else
435 \@tempskipb\subfig@top\relax\@xaddvskip
436 \fi
437 \fi
438 \if@contbotsub
439 \box\@tempboxa\egroup
440 \ifx \@empty#3\relax \else
441 \vskip\subfigcapskip
442 \@subcaption{#1}{#2}{#3}%
443 \fi
444 \else
445 \ifx \@empty#3\relax \else
446 \@subcaption{#1}{#2}{#3}%
447 \vskip\subfigcapskip
448 \vskip\subfigcaptopadj
449 \fi\egroup
450 \box\@tempboxa
451 \fi
452 \vspace{\subfig@bottom}
453 \egroup
454 \egroup}
455

```

`\cont@subfig@oldcaption` Keep the definition of `\@caption`.

```

456 \let\cont@subfig@oldcaption\@caption
457

```

The remainder of the `subfigure21` option code.

`\doxxi@contcaption` This command redefines the `\@contcaption` command to flush out any pending subcaptions. The redefinition cannot be done within `\if...\fi` because of the internal `\if...` creation. The code is simplified from the `subfigure v2.1` redefinition of `\@caption`.

```

458 \newcommand{\doxxi@contcaption}{%
459 \long\def\@contcaption##1##2{%
460 \if@contbotsub
461 \@listsubcaptions{##1}%
462 \subfigold@contcaption{##1}{##2}
463 \else
464 \subfigold@contcaption{##1}{##2}
465 \@listsubcaptions{##1}%
466 \fi}
467 }
468

```

We can now call the rest of the subfigure21 code, if required.

```

469 %%%\if@contsubfigxxi
470
\subbottom \subbottom[<list-entry>][<subcaption>]{<text>} typesets a subcaption below the
\@contsubbody <text>. Most of the work is performed by the \@contsubbody macro.
471 \newcommand{\subbottom}{%
472   \@contbotsubtrue
473   \@contsubbody}
474
475 \newcommand{\@contsubbody}{%
476   \bgroup
477   \let\subfig@oldlabel=\label
478   \let\label=\sub@label
479   \if@contmaincaption\else
480     \advance\csname c@\@capttype\endcsname\@ne
481     \fi
482     \refstepcounter{sub\@capttype}\@contkeep%
483     \leavevmode
484     \@ifnextchar [%
485       {\@@contsubfloat}%
486       {\@@contsubfloat[\@empty]}}
487
\contsubbottom These are the continued versions of \subbottom and \@contsubbody.
\subbody@cont 488 \newcommand{\contsubbottom}{%
489   \@contbotsubtrue
490   \subbody@cont}
491
492 \newcommand{\subbody@cont}{%
493   \bgroup
494   \let\subfig@oldlabel=\label
495   \let\label=\sub@label
496   \@contset
497   \refstepcounter{sub\@capttype}\@contkeep%
498   \leavevmode
499   \@ifnextchar [%
500     {\@@contsubfloat}%
501     {\@@contsubfloat[\@empty]}}
502

\subtop These are similar to \subbottom and \contsubbottom except that they put the
\contsubtop subcaption on top of the <text>.
503 \newcommand{\subtop}{%
504   \@contbotsubfalse
505   \@contsubbody}
506
507 \newcommand{\contsubtop}{%
508   \@contbotsubfalse

```

```

509     \subbody@cont}
510
\contsubfigure This a simplified version of \subfigure in that the main caption counter is not
                incremented (we should be in a continued float), and the subcounter is restored
                before being incremented.
511     \newcommand{\contsubfigure}{%
512         \bgroup
513         \let\subfig@oldlabel=\label
514         \let\label=\sub@label
515         \@contset
516         \refstepcounter{sub\@capttype}\@contkeep%
517         \ifnextchar [%
518             {\@@contsubfloat}%
519             {\@@contsubfloat[\@empty]}}
520
\@contsf These are versions of the \subfigure and \subtable macros written using the
\@contst ccaption style.
521 \newcommand{\@contsf}{\@contbotsubtrue%
522   \ifsubfiguretopcap\@contbotsubfalse\fi%
523   \@contsubbody}
524 \newcommand{\@contst}{\@contbotsubtrue%
525   \ifsubtabletopcap\@contbotsubfalse\fi%
526   \@contsubbody}
527
    Now these can be used if appropriate within the \AtBeginDocument code. But
    first call for the new version of \@contcaption.
528 \if@contsubfigxxi
529
530     \doxxi@contcaption
531
532     \AtBeginDocument{%
533         \let\@subfloat\@@@contsubfloat
534         \let\@subfigure\@@@contsubfloat
535         \let\subfigure\@contsf
536         \let\subtable\@contst
537         \let\contsubfigure\contsubbottom
538         \let\contsubtable\contsubtop
539         \long\def\@caption#1[#2]#3{%
540             \cont@subfig@oldcaption{#1}[{#2}]{#3}}
541     }
542
    The end of the subfigure21 option code.
543 \fi
544

```

3.6 New floats

To define a float environment, say `fenv`, the following macros must be defined:

- `\fps@fenv` The default placement specifier (normally `tbp`).
- `\ftype@fenv` The type number which is an integer and a power of 2.
- `\ext@fenv` The file extension for the contents list.
- `\c@fenv` A counter for the environment (for caption numbering).
- `\fnum@fenv` A macro to generate the caption ‘number’.
- `\l@fenv` A macro to produce an entry in a list of. . .
- `\flegtoc@fenv` A macro to write a `\namedlegend` title to a listof file.
- `\fleg@fenv` A macro to typeset the name of a `\namedlegend`.
- `\toclevel@fenv` Holding a bookmark level.

Note that the `\fleg. . .` macros are only required for the `ccaption` package, and `\toclevel@fenv` is only required if the `hyperref` package is being used. The others are required for any new float, whether or not the `ccaption` package is being used.

`newflo@tctr` A counter for the type number of a new float. Normally figures are of type 1, tables type 2, and the next float type is then 4, and so on.

```
545 \newcounter{newflo@tctr}
546 \ifundefined{c@figure}{\setcounter{newflo@tctr}{1}}{
547   \ifundefined{c@table}{\setcounter{newflo@tctr}{2}}{
548     \setcounter{newflo@tctr}{4}}
549
```

`\cftdot` These macros are also provided by the `tocloft` package, but we need them in any event.

```
\cftdotsep
\cftdotfill 550 \providecommand{\cftdot}{.}
\@cfttocstart 551 \providecommand{\cftdotsep}{4.5}
\@cfttocfinish 552 \providecommand{\cftdotfill}[1]{%
553   \leaders\hbox{$\m@th\mkern #1 mu \hbox{\cftdot}\mkern #1 mu$}\hfill}
554 \providecommand{\@cfttocstart}{%
555   \ifundefined{chapter}{}{%
556     \if@twocolumn
557       \@restonecoltrue\onecolumn
558     \else
559       \@restonecolfalse
560     \fi}}
561 \providecommand{\@cfttocfinish}{%
562   \ifundefined{chapter}{}{\if@restonecol\twocolumn\fi}}
563
```

`\newfloatentry` `\newfloatentry[<within>]{<counter>}{<ext>}{<level-1>}` generates the commands for typesetting a caption in a float and a caption in a listing.

564 `\newcommand{\newfloatentry}[4][\@empty]{%`

`\c@X` Create the new counter. An error if it exists.

```

\theX 565 \ifundefined{c@#2}{%
566     \ifx \@empty#1\relax
567     \newcounter{#2}
568     \else
569     \ifundefined{c@#1}{\PackageWarning{ccaption}%
570         {#1 has no counter for use as a 'within'}
571     \newcounter{#2}}%
572     {\newcounter{#2}[#1]%
573     \expandafter\edef\csname the#2\endcsname{%
574     \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}}}
575     \fi
576     \setcounter{#2}{0}
577 }
578 {\PackageError{ccaption}{#2 has been previously defined}{\@eha}}
579

```

That finishes off the error checking, rest is defined in any event

`\l@X` `\l@X{title}{page}` typesets the entry in the listing, but only if the Zdepth is greater than *<level-1>*.

```

580 \namedef{l@#2}##1##2{%
581     \ifnum \@nameuse{c@#3depth} > #4\relax
582     \vskip \@nameuse{cftbefore#2skip}
583     {\leftskip \@nameuse{cft#2indent}\relax
584     \rightskip \@tocrmarg
585     \parfillskip -\rightskip
586     \parindent \@nameuse{cft#2indent}\relax\@afterindenttrue
587     \interlinepenalty\@M
588     \leavevmode
589     \@tempdima \@nameuse{cft#2numwidth}\relax
590     \expandafter\let\expandafter\@cftbsnum\csname cft#2presnum\endcsname
591     \expandafter\let\expandafter\@cftasnum\csname cft#2aftersnum\endcsname
592     \expandafter\let\expandafter\@cftasnumb\csname cft#2aftersnumb\endcsname
593     \advance\leftskip\@tempdima \null\nobreak\hskip -\leftskip
594     {\@nameuse{cft#2font}##1}\nobreak
595     \@nameuse{cft#2fillnum}{##2}}
596 \fi
597 } % end of \l@#2
598

```

Now define all the layout commands used by `\l@X`. The default values for these correspond to those for figure and table entries.

`\cftbeforeXskip`

```

599 \expandafter\newlength\csname cftbefore#2skip\endcsname
600 \setlength{\@nameuse{cftbefore#2skip}}{\z@ \@plus .2\p@}

\cftXindent
\cftXnumwidth 601 \expandafter\newlength\csname cft#2indent\endcsname
602 \expandafter\newlength\csname cft#2numwidth\endcsname

Set the default values for the indent and numwidth depending on the entry's level.
A level of 1 ( $\langle level-1 \rangle = 0$ ) corresponds to a figure.

603 \ifcase #4\relax % 0
604 \setlength{\@nameuse{cft#2indent}}{1.5em}
605 \setlength{\@nameuse{cft#2numwidth}}{2.3em}
606 \or % 1
607 \setlength{\@nameuse{cft#2indent}}{3.8em}
608 \setlength{\@nameuse{cft#2numwidth}}{3.2em}
609 \or % 2
610 \setlength{\@nameuse{cft#2indent}}{7.0em}
611 \setlength{\@nameuse{cft#2numwidth}}{4.1em}
612 \or % 3
613 \setlength{\@nameuse{cft#2indent}}{10.0em}
614 \setlength{\@nameuse{cft#2numwidth}}{5.0em}
615 \else % anything else
616 \setlength{\@nameuse{cft#2indent}}{1.5em}
617 \setlength{\@nameuse{cft#2numwidth}}{2.3em}
618 \fi

\cftXfont And the rest of the commands
\cftXpresnum 619 \@namedef{cft#2font}{\normalfont}
\cftXaftersnum 620 \@namedef{cft#2presnum}{\@nameuse{cft#2font}}
\cftXaftersnumb 621 \@namedef{cft#2aftersnum}{\@nameuse{cft#2font}}
\cftXdotsep 622 \@namedef{cft#2aftersnumb}{\@nameuse{cft#2font}}
\cftXleader 623 \@namedef{cft#2dotsep}{\cftdotsep}
\cftXpagefont 624 \@namedef{cft#2leader}{\normalfont\cftdotfill{\@nameuse{cft#2dotsep}}}
\cftXafterpnum 625 \@namedef{cft#2pagefont}{\normalfont}
626 \@namedef{cft#2afterpnum}{\par}

\cftXfillnum This typesets the leader and the page number.
627 \@namedef{cft#2fillnum}##1{%
628 {\@nameuse{cft#2leader}}\nobreak
629 \hb@xt@{\@pnumwidth}{\hfil\@nameuse{cft#2pagefont}##1}%
630 \@nameuse{cft#2afterpnum}\par}

\toclevel@X This is required for the hyperref package.
631 \@namedef{toclevel@#2}{#4}

The end of \newfloatentry
632 } % end \newfloatentry
633

```

```

\newfloatlist \newfloatlist[<within>]{<fenv>}{<ext>}{<listname>}{<capname>} creates the com-
mands for a new float environment <fenv> (aka X) and a new List of for <fenv>,
using <ext> (aka Z) as the file extension.
634 \newcommand{\newfloatlist}[5][\@empty]{%
    Call \newfloatentry[within]{X}{Z}{0} to set up for typesetting the entry.
635 \ifx \@empty#1\relax
636     \newfloatentry{#2}{#3}{0}
637 \else
638     \newfloatentry[#1]{#2}{#3}{0}
639 \fi

\ftype@X Define the float type, set it to the float counter, and double the counter afterwards.
640 \@namedef{ftype@#2}{\value{newflo@tctr}}
641 \addtocounter{newflo@tctr}{\value{newflo@tctr}}

\ext@X Define \ext@X for the file extension and set the new Zdepth depth counter to 1.
Zdepth 642 \@namedef{ext@#2}{#3} % file extension
643 \newcounter{#3depth}
644 \setcounter{#3depth}{1}
645

\cftmarkZ \cftmarkZ specifies the marks for the page headings for the new listing.
646 \@namedef{cftmark#3}{%
647     \mkboth{\MakeUppercase{#4}}{\MakeUppercase{#4}}}
648

\listofX \listofX typesets the listing.
649 \if@conttitleopt
    For the titles option, basically copy the code from the standard \tableofcontents
    command definition.
650 \@namedef{listof#2}{%
651     \cfttocstart
652     \@ifundefined{chapter}{\section*{#4}}{\chapter*{#4}}
653     \@nameuse{cftmark#3}
654     \@starttoc{#3}%
655     \cfttocfinish}
656 \else
    Otherwise, provide a fully parameterised heading style.
657 \@namedef{listof#2}{%
658     \cfttocstart
659     \par
660     \begingroup
661         \parindent\z@ \parskip\z@
662         \@nameuse{@cftmake#3title}
663         \@starttoc{#3}%
664     \endgroup
665     \cfttocfinish}

```

```

666 \fi
667

\@cftmakeZtitle \@cftmakeZtitle typeset the title heading for the liusting.
668 \@namedef{@cftmake#3title}{%
669     \ifundefined{chapter}{%
670         \vspace{@\nameuse{cftbefore#3titleskip}}{%
671             \vspace*{@\nameuse{cftbefore#3titleskip}}
672             \interlinepenalty\M
673             {\@nameuse{cft#3titlefont}#4}{\@nameuse{cftafter#3title}}
674             \@nameuse{cftmark#3}
675             \par\nobreak
676             \vskip \@nameuse{cftafter#3titleskip}
677             \@afterheading}
678

\cftbeforeZtitleskip Define the lengths and commands for controlling the title heading layout. The
\cftafterZtitleskip values depend on whether the document is chaptered or not.
\cftZtitlefont 679 \expandafter\newlength\csname cftbefore#3titleskip\endcsname
\cftafterZtitle 680 \expandafter\newlength\csname cftafter#3titleskip\endcsname
681 \@ifundefined{chapter}{%
682     \setlength{@\nameuse{cftbefore#3titleskip}}{3.5ex \@plus 1ex \@minus .2ex}
683     \setlength{@\nameuse{cftafter#3titleskip}}{2.3ex \@plus .2ex}
684     \@namedef{cft#3titlefont}{\normalfont\Large\bfseries}
685 }{%
686     \setlength{@\nameuse{cftbefore#3titleskip}}{50pt}
687     \setlength{@\nameuse{cftafter#3titleskip}}{40pt}
688     \@namedef{cft#3titlefont}{\normalfont\Huge\bfseries}
689 }
690 \@namedef{cftafter#3title}{}
691

\fps@X \fps@X is the default float placement specification, \fnum@X typesets the caption
\fnun@X name and number, and \flegtoc@X is for named legends.
\flegtoc 692 \@namedef{fps@#2}{tbp} % position
693 \@namedef{fnum@#2}{#5~\@nameuse{the#2}} % caption naming
694 \@namedef{flegtoc@#2}##1{} % named legend
695

X Finally define the new float environment, in both normal and starred forms.
X* 696 \newenvironment{#2}{\@float{#2}}{\end@float}
697 \newenvironment{#2*}{\@dblfloat{#2}}{\end@dblfloat}

This ends the definition of \newfloatlist.
698 } % end \newlistof
699

\newfloatenv Up to version 2.7 of the package the command \newfloatenv[within]{fenv}{ext}{capname}
created a new float environment. It was replaced in later versions by \newfloatlist.
Print a warning message if it is used.

```

```

700 \newcommand{\newfloatenv}[4][\@empty]{%
701   \PackageError{ccaption}{\protect\newfloatenv\space has been replaced
702     by\MessageBreak
703     \protect\newfloatlist}{\@eha}
704 }
705

```

`\listfloats` Up to version 2.7 the `\listfloats{⟨fenv⟩}{⟨heading⟩}` command produced a list of floats for `⟨fenv⟩`. It was replaced in later versions by the generated command `\listoffenv`. Print an error message.

```

706 \newcommand{\listfloats}[2]{%
707   \PackageError{ccaption}{\protect\listfloats{#1}{...} has been
708     replaced by\MessageBreak
709     \protect\listof #1}{\@eha}
710 }
711

```

To define subcaptions for use in a new float environment, say `fenv`, the following macros must be defined [Coc95]:

- A new counter `subfenv` for subcaption numbering.
- A new counter `extdepth`, where `ext` is the file extension for the contents list of `fenv`, for setting the contents depth.
- `\thesubfenv` for the formatting of the subcaption number.
- `\@thesubfenv` for typesetting the number.
- `\@@thesubfenv` for alternative label reference.
- `\p@subfenv` for prepending to the subcaption number when it is referenced.
- `\ext@subfenv` the file extension for the contents list.
- `\l@subfenv` for formatting the contents list entry.
- `\@makesubfenvcaption` for typesetting the subcaption.
- `\toclevel@subfenv` for hyperref bookmarks

`\newsfloat` `\newsfloat{⟨fenv⟩}` creates the commands for a new subfloat for `⟨fenv⟩` (aka X).

```

712 \newcommand{\newsfloat}[1]{%
    Call \newfloatentry[X]{subX}{extX}{1} to get most of the work done.
713   \newfloatentry{#1}{sub#1}{\@nameuse{ext@#1}}{1}

```

```

\ext@subX And now for the rest of the commands for subcaptions.
\thesubX 714 \namedef{ext@sub#1}{\csname ext@#1\endcsname}
\@thesubX 715 \namedef{thesub#1}{(\alph{sub#1})}
\@@thesubX 716 \namedef{thesub#1}{\subcaplabelfont\@nameuse{thesub#1}\space}
\p@subX 717 \namedef{p@thesub#1}{\@nameuse{thesub#1}}
\@makesubXcaption 718 \namedef{p@sub#1}{\csname the#1\endcsname}
719 \namedef{makesub#1caption}{\@makesubfigurecaption}
720 }
721

\newfloatpagesoff \newfloatpagesoff{<fenv>} switches off page numbers in the listing for entries
of type <fenv>. It does this by redefining the \cftXfillnum command.
722 \DeclareRobustCommand{\newfloatpagesoff}[1]{
723 \namedef{cft#1fillnum}##1{%
724 \parfillskip=\z@ plus1fil\@nameuse{cft#1afterpnum}\par}}
725

\newfloatpageson \newfloatpageson{<fenv>} switches on page numbers in the listing for entries of
type <fenv>. It does this by redefining the \cftXfillnum command to its default
specification.
726 \DeclareRobustCommand{\newfloatpageson}[1]{
727 \namedef{cft#1fillnum}##1{%
728 {\@nameuse{cft#1leader}}\nobreak
729 \hb@xt@{\pnumwidth}{\hfil\@nameuse{cft#1pagefont}##1}%
730 \@nameuse{cft#1afterpnum}\par}}
731

\setnewfloatindents \setnewfloatindents{<fenv>}{<indent>}{<width>} sets the indent and numwidth
for the float entry <fenv>.
732 \newcommand{\setnewfloatindents}[3]{%
733 \setlength{\@nameuse{cft#1indent}}{#2}
734 \setlength{\@nameuse{cft#1numwidth}}{#3}
735 }
736

The end of this package.
737 </usc>

```

A The perils of empty

My original code for the \if@contemptyarg command was as follows:

```

\newcommand{\if@contemptyarg}[3]{%
\edef\@conttemp{\zap@space#1 \@empty}
\ifx\@empty\@conttemp\relax #2\else #3\fi}

```

This uses the `\zap@space` kernel command and I wrote the code after looking at various code bits in the kernel and other packages, but I can't now remember which ones.

Donald Arseneau kindly pointed out the error of my ways and provided the robust solution which is used in the body of this package. The following is a slightly edited version of an email he sent me on the subject.

I'm not sure how exactly it is *supposed* to work because there are cases for which it will fail spectacularly. [These involved testing an argument that included macros of various forms]

There are several errors I am sure of though:

- You used `\edef` which is *not* allowed in LaTeX — this creates a moving argument without any protection from `\protect`. Fragile commands will produce stack overflows and other errors. Even if you use `\protected@edef`, as is correct, you still make a moving argument to no purpose.
- `\zap@space` is not valid for general arguments. It fails if it ever sees an empty macro following a space. [e.g., `\def\none{} used as \if@contemptyarg{ \none}{}{}`]
- By making `\if@contemptyarg` skip over one of its parameters (`#2`, `#3`) you make it fail for nesting tabular or array environments.
- `\if@contemptyarg` is itself a fragile command, and will require `\protect` if it ever appears in a title or other moving argument. Since it is possible to do the test by expandable operations alone, it should be done that way.

I suggest you read `CTAN:tex-archive/info/aro-bend/answer.002` for a past discussion of detecting empty arguments, and then use a definition of `\if@contemptyarg` based on that discussion. You'll find it in `amsgen.dtx`, or use instead the improved version . . .

The definition of `\if@contemptyarg` is based on the improved version that Donald supplied, only the macro names being changed.

References

- [Coc95] Steven Douglas Cochran. *The subfigure package*. February 2002. (Available from CTAN as file `subfigure.dtx`)
- [GMS94] Michel Goossens, Frank Mittelbach, and Alexander Samarin. *The LaTeX Companion*. Addison-Wesley Publishing Company, 1994.
- [Lin95] Anselm Lingnau. *An Improved Environment for Floats*. March 1995. (Available from CTAN as file `float.dtx`)
- [McCG95] James Darrell McCauley and Jeff Goldberg. *The endfloat package*. October 1995. (Available from CTAN as file `endfloat.dtx`)

- [NiGa98] Rolf Niepraschk and Hubert Gäßlein. *The sidecap package*. June 1998. (Available from CTAN as file `sidecap.dtx`)
- [Rec97] Keith Reckdahl. *Using Imported Graphics in LaTeX2e*. December 1997. (Available from CTAN as file `info/epslatex.ps` or `info/epslatex.pdf`)
- [Som95] Harald Axel Sommerfeldt. *The caption package*. October 1995. (Available from CTAN as file `caption2.dtx`)
- [Wil96] Peter R. Wilson. *LaTeX for standards: The LaTeX package files user manual*. NIST Report NISTIR, June 1996.
- [Wil01] Peter R. Wilson. *The tocloft package*. March 2001. (Available from CTAN as file `tocloft.dtx`)

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	<code>\cfttocfinish</code>	<code>\@contindenttrue</code> . . 67
<code>\@@@contsubfloat</code> 550, 655, 665	<code>\@contindw</code> <u>64</u> , 102
. 402, 403, <u>405</u> , 533	<code>\cfttocstart</code>	<code>\@contkeep</code>
<code>\@@cont@subfloat</code> <u>550</u> , 651, 658	. <u>247</u> , 333, 346,
. 397, 398	<code>\@contbotsubfalse</code> .	395, 482, 497, 516
<code>\@@contsubfloat</code> <u>400</u> , 353, 357,	<code>\@contlabel</code> 83, 87
485, 486, 500,	504, 508, 522, 525	<code>\@contmaincaptionfalse</code>
501, 518, 519, 534	<code>\@contbotsubtrue</code> 257,
<code>\@@thesubX</code> <u>714</u>	. 259, 325, 340,	268, 272, 382, 386
<code>\@afterheading</code> 677	472, 489, 521, 524	<code>\@contmaincaptiontrue</code>
<code>\@afterindenttrue</code> . 586	<code>\@contcapoptionfalse</code> 18	. 264, 266, 378, 380
<code>\@caption</code> . 20, 456, 539	<code>\@contcapoptiontrue</code> 19	<code>\@contmidbi</code> <u>71</u> ,
<code>\@captype</code> . 20, 119–	<code>\@contcaption</code> . 121,	195, 210, 230, 242
121, 151, 172,	<u>123</u> , 252, <u>360</u> , 459	<code>\@contnfont</code> <u>40</u> ,
174, 176, 193,	<code>\@contcstyle</code>	84, 94, 96, 101, 105
194, 209, 213,	. . <u>54</u> , 97, 102, 106	<code>\@contoldc</code>
215, 229, 241,	<code>\@contcwfalse</code> 61	. 263, 264, 377, 378
249–251, 331,	<code>\@contcwidth</code> <u>57</u> , 91	<code>\@contoldcont</code>
333, 336, 337,	<code>\@contcwtrue</code> 60	. 265, 266, 379, 380
346, 349, 350,	<code>\@contdelim</code> <u>37</u> ,	<code>\@contoldf</code>
395, 402, 403,	84, 94, 96, 101, 105	. 267, 270, 381, 384
480, 482, 497, 516	<code>\@contfmark</code> <u>81</u> , 86	<code>\@contoldff</code>
<code>\@cftasnum</code> 591	<code>\@contfnote</code> <u>81</u> , 85	. 271, 274, 385, 388
<code>\@cftasnumb</code> 592	<code>\@conthangfalse</code> . 67, 68	<code>\@contpost</code> <u>71</u> , 109
<code>\@cftbsnum</code> 590	<code>\@conthangtrue</code> 65	<code>\@contpre</code> <u>71</u> , 95, 100, 104
<code>\@cftmakeZtitle</code> . . . <u>668</u>	<code>\@contindentfalse</code> 65, 68	<code>\@contset</code>

. 247, 345, 496, 515	\@makecaption .. 20,	A
\@contsf 521, 535	78, 131, 148, 162	\abovecaptionskip ..
\@contst 521, 536	\@makesubXcaption . 714 21, 79,
\@contsubbody	\@makesubfigurecaption	190, 206, 226, 238
.... 324, 354, 719	\abovelegendskip 9, 134
471, 505, 523, 526	\@minipagefalse ... 430	\addcontentsline ..
\@contsubfigfalse . 10	\@namedef 213, 215, 305, 364
\@contsubfigtrue ..	. 580, 619–627,	\addtocounter
..... 11, 12, 16	631, 640, 642, 119, 194, 641
\@contsubfigxxfalse	646, 650, 657,	\AtBeginDocument ..
..... 6, 12, 16	668, 684, 688, 261, 532
\@contsubfigxxifalse	690, 692–694,	
..... 8, 11	714–719, 723, 727	B
\@contsubfigxxittrue	\@nameuse . 317, 365,	\baselineskip 135
..... 12, 16	581–583, 586,	\belowcaptionskip ..
\@contsubfigxxtrue . 11	589, 594, 595, 21, 114,
\@contsubfloat 391	600, 604, 605,	191, 207, 227, 239
\@conttempa	607, 608, 610,	\belowlegendskip 9, 134
78, 80, 96, 101,	611, 613, 614,	\bicaption 12, 220
105, 362, 363, 367	616, 617, 624,	\bicontcaption . 12, 235
\@conttempc ... 192,	628–630, 653,	\bionenumcaption 11, 200
193, 208, 209,	662, 670, 671,	\bitwonumcaption 11, 184
228, 229, 240, 241	673, 674, 676,	
\@conttfont	682, 683, 686,	C
43, 84, 97, 102, 106	687, 693, 713,	\c@X 565
\@contttitloptfalse 21	716, 717, 724,	\caption 20, 171, 173,
\@contttitlopttrue . 22	728–730, 733, 734	175, 186, 196,
\@currentlabel 312, 313	\@parboxrestore ...	202, 222, 263, 376
\@dbflt 263, 376 126, 142, 157	\captiondelim 4, 37, 147
\@dblarg 151	\@pnumwidth ... 629, 729	\captionnamefont . 4, 40
\@dblfloat 697	\@restonecolfalse . 559	\captionstyle 4, 54
\@eha 578, 703, 709	\@restonecoltrue .. 557	\captiontitlefont 4, 43
\@firstoftwo 180	\@secondoftwo 180	\captionwidth 4, 57
\@float 263, 376	\@setminipage	\catcode 179
\@for 362 128, 144, 159	\centering 88, 90
\@if@contemptyarg .	\@starttoc ... 654, 663	\centerlastline ... 46
.... 178, 186,	\@subcaption .. 285,	\cftafterZtitle 16, 679
196, 202, 212, 222	292, 300, 442, 446	\cftafterZtitleskip
\@ifnextchar	\@subfigcaptionlist 16, 679
. 335, 348, 396, 308,	\cftbeforeXskip 17, 599
401, 484, 499, 517	310, 311, 362, 369	\cftbeforeZtitleskip
\@ifundefined	\@subfigure 534 16, 679
. 269, 273, 383,	\@subfloat 276, 336,	\cftdot 550
387, 546, 547,	337, 349, 350, 533	\cftdotfill ... 550, 624
555, 562, 565,	\@tempskipb 435	\cftdotsep ... 550, 623
569, 652, 669, 681	\@thesubX 714	\cftmarkZ 16, 646
\@legend 151, 153	\@tocrmarg 584	\cftXafterpnum . 18, 619
\@listsubcaptions .	\@xaddvskip 435	\cftXaftersnum . 18, 619
..... 461, 465	\@xif@contmt .. 180, 181	\cftXaftersnumb ... 619
	\\ 5	\cftXaftersnumnb .. 18

<code>\cftXdotsep</code>	18, 619		387, 480, 573,	<code>\ifminipage</code>	
<code>\cftXfillnum</code>	627		574, 590–592,	. 127, 143, 158, 408	
<code>\cftXfont</code>	17, 619		599, 601, 602,	<code>\if@restonecol</code>	562
<code>\cftXindent</code>	17, 601		679, 680, 714, 718	<code>\if@twocolumn</code>	556
<code>\cftXleader</code>	18, 619	environments:		<code>\ifsf@tight</code>	407
<code>\cftXnumwidth</code>	17, 601	<code>X*</code>	696	<code>\ifsubfiguretopcap</code>	522
<code>\cftXpagefont</code>	18, 619	<code>X</code>	16, 696	<code>\ifsubtabletopcap</code>	525
<code>\cftXpresnum</code>	18, 619	<code>\ext@subX</code>	714	<code>\ignorespaces</code>	
<code>\cftZtitlefont</code>	16, 679	<code>\ext@type</code>	20	. 131, 148, 162,	
<code>\changecaptionwidth</code>		<code>\ext@X</code>	642	214, 216, 307, 314	
.	4, 57			<code>\indentcaption</code>	4, 64
<code>\chapter</code>	652	F		<code>\interlinepenalty</code>	587, 672
<code>\cont@subfig@oldcaption</code>		<code>\figurename</code>	169		
.	456, 540	<code>\fleg@figure</code>	168	L	
<code>\contcaption</code>		<code>\fleg@table</code>	168	<code>\l@</code>	597
.	6, 118 , 211, 231,	<code>\fleg@type</code>	9	<code>\l@X</code>	580
237, 243, 263 , 376		<code>\flegtoc</code>	692	<code>\label</code> 83, 87, 188, 204,	
<code>\contsubbottom</code>	13,	<code>\flegtoc@figure</code>	165	224, 302, 393,	
339, 372, 488 , 537		<code>\flegtoc@table</code>	165	394, 477, 478,	
<code>\contsubfigure</code>		<code>\flegtoc@type</code>	10	494, 495, 513, 514	
.	371 , 511 , 537	<code>\flushleft</code>	46	<code>\Large</code>	684
<code>\contsubtable</code>	371 , 538	<code>\fnum@type</code>	20	<code>\lastskip</code>	411, 434
<code>\contsubtop</code>	13,	<code>\fnum@X</code>	692	<code>\leaders</code>	553
356, 371, 503 , 538		<code>\footnote</code>	81, 85	<code>\leftskip</code> 47, 50, 583, 593	
<code>\csname</code> 131, 155, 162,		<code>\footnotemark</code>	82, 86	<code>\legend</code>	7, 139
193, 209, 213,		<code>\fps@X</code>	692	<code>\linewidth</code>	59, 88
215, 229, 241,		<code>\ftype@X</code>	640	<code>\listfloats</code>	19, 706
269, 273, 305,				<code>\listof</code>	709
306, 331, 383,		H		<code>\listofX</code>	16, 649
387, 480, 573,		<code>\hangafter</code>	97, 102		
574, 590–592,		<code>\hangcaption</code>	4, 64	M	
599, 601, 602,		<code>\hb@xt@</code>	629, 729	<code>\MakeUppercase</code>	647
679, 680, 714, 718		<code>\Huge</code>	688	<code>\mbox</code>	147
				<code>\MessageBreak</code>	
D		I		14, 32, 33, 702, 708	
<code>\DeclareRobustCommand</code>		<code>\if@contbotsub</code> 258 ,		<code>\midbicaption</code>	13, 71
.	722, 726	279, 418, 438, 460		<code>\mkern</code>	553
<code>\do</code>	362	<code>\if@contcaption</code>			
<code>\doxxi@contcaption</code>	17 , 30, 116	N	
.	458, 530	<code>\if@contcw</code>	26 , 89, 110	<code>\namedlegend</code>	9, 151
E		<code>\if@conthang</code>	26 , 93	<code>\newfixedcaption</code> 10 , 171	
<code>\edef</code>	192,	<code>\if@contindent</code>	26 , 99	<code>\newflo@tctr</code>	545
208, 228, 240, 573		<code>\if@contmaincaption</code>		<code>\newfloatentry</code>	17,
<code>\endcsname</code> 256 , 304, 330, 479		564 , 636, 638, 713	
. 131, 155, 162,		<code>\if@contsubfig</code>	5 , 247	<code>\newfloatenv</code>	19, 700
193, 209, 213,		<code>\if@contsubfigxx</code>	5 , 262, 323	<code>\newfloatlist</code>	
215, 229, 241,		<code>\if@contsubfigxxi</code>	15, 634 , 703
269, 273, 305,		5 , 376, 469, 528	<code>\newfloatpagesoff</code>	19, 722
306, 331, 383,		<code>\if@conttitleopt</code> 20 , 649		<code>\newfloatpageson</code> 19, 726	

<code>\newif</code> ... 5, 7, 9, 17, 20, 26–28, 256, 258	<code>\ProvidesPackage</code> ... 3	<code>\subfigold@contcaption</code> ... 247 , 361, 462, 464
<code>\newlistof</code> 698	Q	<code>\subfigtopskip</code> 281, 294, 419, 423
<code>\newsfloat</code> ... 19, 712	<code>\Q</code> 179	<code>\subfigure</code> ... 319 , 535
<code>\noexpand</code> 314, 574	R	<code>\subtable</code> 319 , 536
<code>\normalcaption</code> ... 4, 64	<code>\renewfixedcaption</code> 10, 171	<code>\subtop</code> 13, 320, 352 , 503
<code>\normalcaptionwidth</code> 4, 57	S	<code>\suppressfloats</code> ... 26
<code>\normalfont</code> ... 619, 624, 625, 684, 688	<code>\sbox</code> 84, 94	T
<code>\normalsize</code> 130, 146, 161	<code>\section</code> 652	<code>\tablename</code> 168
O	<code>\setnewfloatindents</code> 18, 732	<code>\thesubX</code> 714
<code>\onecolumn</code> 557	<code>\string</code> 303, 312	<code>\theX</code> 17, 565
P	<code>\sub@label</code> 394, 478, 495, 514	<code>\toclevel@subfigure</code> 253
<code>\p@subX</code> 714	<code>\subbody@cont</code> 339 , 358, 488 , 509	<code>\toclevel@subtable</code> . 253
<code>\PackageError</code> 578, 701, 707	<code>\subbottom</code> 13, 319, 324 , 471	<code>\toclevel@X</code> 631
<code>\PackageWarning</code> ... 569	<code>\subcaplabelfont</code> .. 716	<code>\topskip</code> 80
<code>\PackageWarningNoLine</code> 13, 31	<code>\subconcluded</code> .. 13, 247	<code>\twocolumn</code> 562
<code>\parbox</code> 91	<code>\subfig@bottom</code> 420, 423, 452	V
<code>\parindent</code> ... 586, 661	<code>\subfig@oldlabel</code> 393, 477, 494, 513	<code>\value</code> 249, 250, 640, 641
<code>\parskip</code> 661	<code>\subfig@top</code> 419, 422, 432, 435	<code>\vbox</code> .. 80, 281, 294, 428
<code>\postcaption</code> 4, 71	<code>\subfigbottomskip</code> 287, 296, 420, 422	<code>\vtop</code> 280, 289, 427
<code>\precaption</code> 4, 71	<code>\subfigcapskip</code> 284, 291, 441, 447	X
<code>\prevdepth</code> 79	<code>\subfigcaptopadj</code> .. 448	<code>\X</code> 17
<code>\ProcessOptions</code> ... 23		<code>X</code> (environment) . 16, 696
<code>\providecommand</code> 176, 253, 254, 550–552, 554, 561		<code>X*</code> (environment) ... 696
<code>\providefixedcaption</code> 10, 171		<code>\xdef</code> 310
		Z
		<code>\Zdepth</code> 16, 642